



# LOW VOLTAGE DIRECTIVE TEST REPORT

*For*

**RED LIGHT THERAPY CAP**

**Model: QZ022, QZ036**

**Brand Name: N/A**

**Report No.: ENC2510105GZ18L1**

**Date of Issue: Oct. 20, 2025**

*Prepared For*

**Shenzhen Liyoutong Technology Co., Ltd.**

**2/F, Block C, Baoshan Second Industrial Zone, Pingshan District, Shenzhen,  
Guangdong, China**

*Prepared By*

**East Notice Certification Service Co., Ltd.**

**1/F, Haohui Commercial Building, Zhuji Street, Dongpu Town, Tianhe District,  
Guangzhou City, China**

E-mail: [enc@enc-lab.com](mailto:enc@enc-lab.com)

Web: [www.enc-lab.com](http://www.enc-lab.com)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



1/F, Haohui Commercial Building, Zhuji Street, Dongpu Town, Tianhe District, Guangzhou City  
E-mail: [enc@enc-lab.com](mailto:enc@enc-lab.com)    [Http:// www.enc-lab.com](http://www.enc-lab.com)

**TEST REPORT****EN 60335-2-27****Household and similar electrical appliances - Safety - Part 2-27: Particular requirements for appliances for skin exposure to ultraviolet and infrared radiation**

Report reference No. .... : ENC2510105GZ18L1

Tested by ..... : Sam Liu

Review by (+ Signature). .... : Yemig

Approved by (+ signature) ..... : Ray Zhou

Date of issue ..... : Oct. 20, 2025

Contents ..... : Total 68 pages

**Testing laboratory**

Name ..... : East Notice Certification Service Co., Ltd.

Address ..... : 1/F, Haohui Commercial Building, Zhuji Street, Dongpu Town,  
Tianhe District, Guangzhou City, China

Testing location ..... : Same as above

**Application**

Name..... : Shenzhen Liyoutong Technology Co., Ltd.

Address ..... : 2/F, Block C, Baoshan Second Industrial Zone, Pingshan  
District, Shenzhen, Guangdong, China**Manufacturer**

Name..... : Shenzhen Liyoutong Technology Co., Ltd.

Address..... : 2/F, Block C, Baoshan Second Industrial Zone, Pingshan  
District, Shenzhen, Guangdong, China**Test specification**Standard ..... : EN 60335-2-27:2013+A2:2020  
EN IEC 60335-1:2023+A11:2023  
EN 62233:2008

Test procedure ..... : CE- LVD 2014/35/EU

Procedure deviation ..... : N/A

Non-standard test method ..... : N/A

**Test Report Form/blank test report**

Test Report Form No. .... : ENC60335-2-27A23

TRF originator. .... : ENC

**Test item**

Description ..... : RED LIGHT THERAPY CAP

Brand name ..... : N/A

Model and/or type reference ..... : QZ022, QZ036

Rating(s) ..... : DC 5V, 0.3A by USB port or built-in lithium ion battery  
(2000mAh)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**Test case verdicts**

Test case does not apply to the test object.....: N(/A)

Test item does meet the requirement .....: P(ass)

Test item does not meet the requirement.....: F(ail)

**Testing**

Date of receipt of test item .....: Oct. 10, 2025

Date(s) of performance of test .....: Oct. 10, 2025 - Oct. 20, 2025

**General remarks**

This test report shall not be reproduced except in full without the written approval of the testing laboratory.

The test results presented in this report relate only to the item tested.

"(see remark #)" refers to a remark appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a comma is used as the decimal separator.

When determining the test result, measurement uncertainty has been considered.

Note:

This report shall not be altered, increase and deleted.

The results relate only to the items tested.

This report shall not be published as advertisement without the approval of ENC.

This report shall not be copied partly without the written approval of ENC.

Should any objections to the test reports occurred, should submit it to the Company within ten days since the issuing of the report, Fail to accept.

**Special description:**

1. All tests are basic on model QZ022.
2. All models have same electrical structure as QZ022, except for the different appearance and power.
3. Specified maximum ambient temperature is 40°C.

**Summary of testing**

All tests were found satisfactory in accordance with EN 60335-2-27:2013+A2:2020, EN IEC 60335-1:2023+A11:2023, EN 62233:2008.

**Marking on the appliance:**

Remark:

The height of mark shall be at least 7mm.

The additional markings which do not give rise to misunderstanding maybe added.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                         |        |         |
|---------------|-----------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                      | Result | Verdict |
| <b>5</b>      | <b>GENERAL CONDITIONS FOR THE TESTS</b>                                                 |        | --      |
| 5.1           | Tests performed according to cl. 5, e.g. nature of supply, sequence of testing, etc.    |        | P       |
|               | Appliances with IR emitters only are tested as heating appliances. (EN 60335-2-27)      |        | P       |
| 5.2           | The tests are carried out on two appliances, identified as appliance A and appliance B. |        | N       |


|          |                                                                                                                                                      |           |    |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----|
| <b>6</b> | <b>CLASSIFICATION</b>                                                                                                                                |           | -- |
| 6.1      | Protection against electric shock: Class I, II, III .....                                                                                            | Class III | -- |
| 6.2      | Protection against harmful ingress of water                                                                                                          | IPX0      | -- |
| 6.101    | UV appliances shall be one of the following types with respect to the emission of ultraviolet radiation: (EN 60335-2-27)                             |           | -- |
|          | – appliances for household use; (EN 60335-2-27)                                                                                                      |           | P  |
|          | – appliances for commercial use only. (EN 60335-2-27)                                                                                                |           | N  |
|          | NOTE 1 Appliances for household use may also be for commercial use, such as in tanning salons, beauty parlours and similar premises. (EN 60335-2-27) |           | P  |
|          | NOTE 2 Detailed classification of the appliances is described in Annex BB. (EN 60335-2-27)                                                           |           | P  |

|          |                                                                                                                              |                                         |    |
|----------|------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|----|
| <b>7</b> | <b>MARKING AND INSTRUCTIONS</b>                                                                                              |                                         | -- |
| 7.1      | Appliances shall be marked with the                                                                                          |                                         | P  |
|          | Rated voltage or voltage range(V)                                                                                            | DC 5V                                   | P  |
|          | Symbol for nature of supply                                                                                                  | ==                                      | P  |
|          | Rated current(A)                                                                                                             | 0.3A                                    | P  |
|          | Rated frequency(Hz)                                                                                                          |                                         | N  |
|          | Rated power input (W)                                                                                                        |                                         | N  |
|          | Name and /or trademark of the manufacturer or supplier:                                                                      | Shenzhen Liyoutong Technology Co., Ltd. | P  |
|          | Model or type reference                                                                                                      | QZ022                                   | P  |
|          | Symbol 5172 of IEC60417, for class II appliances only;                                                                       |                                         | N  |
|          | IP number according to degree of protection against ingress of water, other than IPX0.                                       | IPX0                                    | N  |
|          | Detachable covers shall be marked with the model or type reference of the appliance with which they are intended to be used. |                                         | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.

| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                                                                       |        |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                                                                                    | Result | Verdict |
|               | UV appliances intended for use in tanning salons, beauty parlours and similar premises shall be marked with the "not for household use" symbol shown in 7.6 or with the substance of the following: (EN 60335-2-27)                                                                                                                                                   |        | N       |
|               | Not for household use (EN 60335-2-27)                                                                                                                                                                                                                                                                                                                                 |        | N       |
|               | Appliances having replaceable UV emitters shall be marked with the type reference of the emitters that are recommended for use. (EN 60335-2-27)                                                                                                                                                                                                                       |        | N       |
|               | Appliances having UV emitters shall be marked with the substance of the following: (EN 60335-2-27)                                                                                                                                                                                                                                                                    |        | N       |
|               | WARNING: Ultraviolet radiation may cause injury to eyes and skin, such as skin aging and eventually skin cancer. Read instructions carefully. Wear the protective goggles provided. Certain medicines and cosmetics may increase sensitivity. (EN 60335-2-27)                                                                                                         |        | N       |
|               | NOTE 102 For appliances having UV emitters intended only for use in tanning salons, beauty parlours and similar premises, this warning may be given on a permanent label intended to be fixed on the wall adjacent to the UV appliance. The wording "Read instructions carefully" may be replaced by "Consult the attendant for further information". (EN 60335-2-27) |        | N       |
|               | Appliances having UV emitters with a luminance exceeding 100 000 cd/m <sup>2</sup> shall be marked with the substance of the following: (EN 60335-2-27)                                                                                                                                                                                                               |        | N       |
|               | WARNING: Intense light. Do not stare at the emitter. (EN 60335-2-27)                                                                                                                                                                                                                                                                                                  |        | N       |
|               | NOTE 103 The method of measuring luminance is given in Annex AA. (EN 60335-2-27)                                                                                                                                                                                                                                                                                      |        | N       |
|               | NOTE 104 If these warnings are combined, the word "warning" need not be repeated. (EN 60335-2-27)                                                                                                                                                                                                                                                                     |        | N       |
| 7.2           | Warning for stationary appliances for multiple supply                                                                                                                                                                                                                                                                                                                 |        | N       |
|               | Warning placed in vicinity of terminal cover                                                                                                                                                                                                                                                                                                                          |        | N       |
| 7.3           | Range of rated values marked with the lower and upper limits separated by a hyphen.                                                                                                                                                                                                                                                                                   |        | N       |
| 7.4           | If the appliance can be adjusted for different rated voltages, the voltage to which the appliance is adjusted shall be clearly discernible.                                                                                                                                                                                                                           |        | N       |
| 7.5           | Appliance with more than one rated voltages or more rated voltages, marked with rated input or rated current for each rated voltage or range, unless                                                                                                                                                                                                                  |        | N       |
| 7.6           | Correct symbols used                                                                                                                                                                                                                                                                                                                                                  | V, A   | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                                                   |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                                                                | Result | Verdict |
|               |  Not for household use (EN 60335-2-27)                                                                                                                                                                                                                           |        | N       |
|               | NOTE 101 This symbol incorporates the prohibition sign of ISO 3864 (EN 60335-2-27)                                                                                                                                                                                                                                                                |        | N       |
| 7.7           | Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply                                                                                                                                                                                                                      |        | N       |
| 7.8           | Except for type Z attachment, terminals used for connection to the supply mains shall be indicated as follows:                                                                                                                                                                                                                                    |        | N       |
|               | - terminals intended exclusively for the neutral conductor shall be indicated by the letter N;                                                                                                                                                                                                                                                    |        | N       |
|               | - protective earthing terminals shall be indicated by symbol 5019 of IEC 60417.                                                                                                                                                                                                                                                                   |        | N       |
| 7.9           | Marking or placing of switches which may cause a hazard.                                                                                                                                                                                                                                                                                          |        | P       |
| 7.10          | The different positions of switches on stationary appliances and the different positions of controls on all appliances shall be indicated by figures, letters or other visual means.                                                                                                                                                              |        | N       |
|               | The figure 0 shall not be used for any other indication unless it is positioned                                                                                                                                                                                                                                                                   |        | N       |
| 7.11          | Indication for direction of adjustment of controls                                                                                                                                                                                                                                                                                                |        | P       |
| 7.12          | Instructions for safe use provided.                                                                                                                                                                                                                                                                                                               |        | P       |
| 7.12.1        | Sufficient details for installation supplied.                                                                                                                                                                                                                                                                                                     |        | N       |
| 7.12.2        | Stationary appliance is not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III conditions, the instructions shall state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules. |        | N       |
| 7.12.3        | Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions stating that the fixed wiring must be protected.                                                                                                                                                                                               |        | N       |
| 7.12.4        | Instructions for built-in appliances                                                                                                                                                                                                                                                                                                              |        | N       |
|               | - dimensions of the space                                                                                                                                                                                                                                                                                                                         |        | N       |
|               | - dimensions and position of the means                                                                                                                                                                                                                                                                                                            |        | N       |
|               | - minimum distances between the various parts and the surrounding structure;                                                                                                                                                                                                                                                                      |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.


| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                |        |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                             | Result | Verdict |
|               | - minimum dimensions of ventilating openings and their correct arrangement;                                                                                                                                                                                                                                    |        | N       |
|               | - connection of the appliance to the supply mains and the interconnection of any separate components;                                                                                                                                                                                                          |        | N       |
|               | - allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring.                                                                                                                                                                                                 |        | N       |
|               | The instructions shall give clear information with regard to the proper use of the appliance.                                                                                                                                                                                                                  |        | --      |
|               | The instructions for appliances having UV emitters shall include the substance of the following: (EN 60335-2-27)                                                                                                                                                                                               |        | N       |
|               | – a statement that UV appliances are not to be used by persons whose skin burns without tanning when exposed to the sun, by persons suffering from sunburn, by children or by persons suffering from or previously suffering from skin cancer or predisposed to skin cancer; (EN 60335-2-27)                   |        | N       |
|               | – a statement that UV appliances are not to be used without taking medical advice if unexpected effects, such as itching, occur within 48 hours of the first session; (EN 60335-2-27)                                                                                                                          |        | N       |
|               | – information concerning the intended exposure distance (unless this is controlled by the construction of the UV appliance); (EN 60335-2-27)                                                                                                                                                                   |        | N       |
|               | – recommended schedule of exposure specifying duration and intervals (based on the UV emitter characteristics, distances and skin sensitivity); (EN 60335-2-27)                                                                                                                                                |        | N       |
|               | NOTE 101 The recommended exposure time for the first session for untanned skin is to correspond to a dose not exceeding $100 \text{ J/m}^2$ , weighted according to the erythema action spectrum shown in Figure 101, or as a result of a test on a small area of the skin. (EN 60335-2-27)                    |        | N       |
|               | – recommended number of exposures that should not be exceeded in one year; (EN 60335-2-27)                                                                                                                                                                                                                     |        | N       |
|               | NOTE 102 The recommended number of exposures for each part of the body is to be based upon a maximum yearly dose of $25 \text{ kJ/m}^2$ , weighted according to the non-melanoma skin cancer action spectrum shown in Figure 101 and taking into account the recommended schedule of exposure. (EN 60335-2-27) |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                    |        |         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                 | Result | Verdict |
|               | – a statement that the appliance must not be used if the timer is faulty or the filter is broken or removed; (EN 60335-2-27)                                                                                                                                                       |        | N       |
|               | – identification of alternative components that may influence the ultraviolet radiation, such as filters and reflectors; (EN 60335-2-27)                                                                                                                                           |        | N       |
|               | – identification of replaceable UV emitters and a statement that they are only to be replaced by the types marked on the appliance, or an instruction that the replacement of lamps must only be carried out after taking advice from an authorized service agent. (EN 60335-2-27) |        | N       |
|               | The instructions for appliances having UV emitters shall contain the substance of the following information and precautions: (EN 60335-2-27)                                                                                                                                       |        | N       |
|               | – ultraviolet radiation from the sun or UV appliances can cause skin or eye damage. These biological effects depend upon the quality and quantity of the radiation as well as the skin and eye sensitivity of the individual; (EN 60335-2-27)                                      |        | N       |
|               | – the skin may develop sunburn after an excessive exposure. Excessively repeated exposures to ultraviolet radiation from the sun or UV appliances may lead to premature aging of the skin as well as increased risk of development of skin tumours; (EN 60335-2-27)                |        | N       |
|               | – the unprotected eye may develop surface inflammation and in some cases, for example after a cataract operation, damage may occur to the retina after excessive exposure. Cataracts may develop after many repeated exposures; (EN 60335-2-27)                                    |        | N       |
|               | – special care is necessary in cases of pronounced individual sensitivity to ultraviolet radiation and in cases where certain medicines or cosmetics are used; (EN 60335-2-27)                                                                                                     |        | N       |
|               | – the following precautions must be taken: (EN 60335-2-27)                                                                                                                                                                                                                         |        | N       |
|               | – always use the protective goggles provided; (EN 60335-2-27)                                                                                                                                                                                                                      |        | N       |
|               | – do not undergo exposure when taking medicines that increase sensitivity to ultraviolet radiation. If in doubt, take medical advice; (EN 60335-2-27)                                                                                                                              |        | N       |
|               | – allow at least 48 hours between the first two exposures; (EN 60335-2-27)                                                                                                                                                                                                         |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                                     |                                          |         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                                                  | Result                                   | Verdict |
|               | - do not sunbathe and use the appliance on the same day; (EN 60335-2-27)                                                                                                                                                                                                                                                            |                                          | N       |
|               | - follow the recommendations concerning exposure durations, exposure intervals and distances from the lamp; (EN 60335-2-27)                                                                                                                                                                                                         |                                          | N       |
|               | - seek medical advice if persistent lumps or sores appear on the skin, or if there are changes in pigmented moles. (EN 60335-2-27)                                                                                                                                                                                                  |                                          | N       |
|               | For appliances having a lid that has to be opened in normal use, the instructions shall include a warning that the appliance must not be switched on with the lid in the closed position and that, before closing the lid for storage, the appliance must be disconnected from the supply and allowed to cool down. (EN 60335-2-27) |                                          | N       |
|               | NOTE 103 This warning is not required if the appliance complies with the tests of 19.2 and 19.3. (EN 60335-2-27)                                                                                                                                                                                                                    |                                          | N       |
|               | The instructions for appliances having IR emitters shall include advice for the protection of the eyes against exposure to infrared radiation and advise that adequate precautions must be taken to safeguard the user against the dangers of excessive exposure. (EN 60335-2-27)                                                   | Eye patch for the protection of the eyes | P       |
|               | If the "not for household use" symbol is used, its meaning shall be explained. (EN 60335-2-27)                                                                                                                                                                                                                                      |                                          | N       |
| 7.12.5        | Replacement cord instructions, type X attachment with a specially prepared cord.                                                                                                                                                                                                                                                    |                                          | N       |
|               | For appliances with type Y attachment                                                                                                                                                                                                                                                                                               |                                          | N       |
|               | For appliances with type Z attachment                                                                                                                                                                                                                                                                                               |                                          | N       |
| 7.12.6        | Caution in the instructions for heating appliances with a non-self-resetting thermal cut-out                                                                                                                                                                                                                                        |                                          | N       |
| 7.12.7        | Instructions for fixed appliances stating how the appliance is to be fixed                                                                                                                                                                                                                                                          |                                          | N       |
| 7.12.8        | Instructions for appliances connected to the water mains:                                                                                                                                                                                                                                                                           |                                          | N       |
|               | - max. inlet water pressure (Pa)                                                                                                                                                                                                                                                                                                    |                                          | N       |
|               | - min. inlet water pressure, if necessary (Pa)                                                                                                                                                                                                                                                                                      |                                          | N       |
|               | Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets                                                                                                                                                                                                                   |                                          | N       |
| 7.12.9        | Instructions specified in 7.12 and from 7.12.1 to 7.12.8 are in hard copy form and appear together before any other instructions supplied with the appliance                                                                                                                                                                        |                                          | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.

| EN 60335-2-27 |                                                                                                                                                                                   |                   |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                | Result            | Verdict |
|               | Alternatively, these instructions may be supplied with the appliance separately from any functional use booklet                                                                   |                   | N       |
|               | They may follow the description of the appliance that identifies parts, or follow the drawings/sketches common to the languages of the instructions                               |                   | N       |
|               | They may follow the description of the appliance that identifies parts, or follow the drawings/sketches                                                                           |                   | N       |
|               | In addition, instructions are also available in an alternative format such as on a website or on request in a format such as a DVD                                                | Website           | P       |
| 7.13          | Instructions and other texts in an official language                                                                                                                              | English language. | P       |
| 7.14          | Marking clearly legible and durable                                                                                                                                               |                   | P       |
|               | The height of the "not for household use" symbol shall be at least 10 mm.                                                                                                         |                   | N       |
| 7.15          | Marking on a main part                                                                                                                                                            |                   | P       |
|               | Marking clearly discernible from the outside, if necessary after removal of a cover                                                                                               |                   | P       |
|               | For portable appliances, cover can be removed or opened without a tool                                                                                                            |                   | N       |
|               | For stationary appliances, name, trademark or identification mark and model or type reference visible after installation                                                          |                   | N       |
|               | For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions                                 |                   | N       |
|               | Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading |                   | N       |
|               | The warnings specified in 7.1 shall be visible after the appliance has been installed and without removal of a cover. (EN 60335-2-27)                                             |                   | P       |
| 7.16          | Marking of possible replaceable thermal link or fuse link clearly visible with regard to replacing the link.                                                                      |                   | N       |

|          |                                                                 |  |    |
|----------|-----------------------------------------------------------------|--|----|
| <b>8</b> | <b>PROTECTION AGAINST ACCESS TO LIVE PARTS</b>                  |  | -- |
| 8.1      | Adequate protection against accidental contact with live parts  |  | P  |
| 8.1.1    | Requirement applies for all positions, detachable parts removed |  | P  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                                         | Result                                                | Verdict |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|---------|
|        | Insertion or removal of lamps, protection against contact with live parts of the lamp cap                                                                                                                  | No such lamp                                          | N       |
|        | Use of test probe B of IEC 61032: no contact with live parts                                                                                                                                               | The test probe can not touch any live with 20N forces | P       |
| 8.1.2  | Use of test probe 13 of IEC 61032 through openings in class 0 appliances and class II appliances/constructions: no contact with live parts                                                                 |                                                       | P       |
|        | Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts                                                                        |                                                       | N       |
| 8.1.3  | For appliances other than class II, use of test probe 41 of IEC 61032: no contact with live parts of visible glowing heating elements                                                                      |                                                       | N       |
| 8.1.4  | Accessible part not considered live if:                                                                                                                                                                    |                                                       | --      |
|        | - safety extra-low a.c. voltage: peak value not exceeding 42,4 V                                                                                                                                           |                                                       | N       |
|        | - safety extra-low d.c. voltage: not exceeding 42,4 V                                                                                                                                                      | DC 5V                                                 | P       |
|        | - or separated from live parts by protective impedance                                                                                                                                                     |                                                       | N       |
|        | If protective impedance: d.c. current not exceeding 2 mA, and a.c. peak value not exceeding 0,7 mA.                                                                                                        |                                                       | N       |
|        | - for peak values over 42,4 V up to and including 450 V, capacitance not exceeding 0,1 $\mu$ F.                                                                                                            |                                                       | N       |
|        | - for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 $\mu$ C.                                                                                                                |                                                       | N       |
| 8.1.5  | Live parts protected at least by basic insulation before installation or assembly: (Check by inspection and the test of 8.1.1)                                                                             |                                                       | --      |
|        | - built-in appliances                                                                                                                                                                                      |                                                       | N       |
|        | - fixed appliances                                                                                                                                                                                         |                                                       | N       |
|        | - appliances delivered in separate units                                                                                                                                                                   |                                                       | N       |
| 8.2    | Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only |                                                       | N       |
|        | Only possible to touch parts separated from live parts by double or reinforced insulation                                                                                                                  |                                                       | N       |
| 8.3    | For battery-operated appliances with a functional earth or supply connection, parts within a battery compartment only accessible if:                                                                       |                                                       | N       |
|        | - class I, 0I and II appliances: separated from live parts by double and reinforced insulation                                                                                                             |                                                       | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                  |        |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                               | Result | Verdict |
|               | - class 0 appliances: separated from live parts by basic insulation                                                              |        | N       |
|               | - battery compartment of class III construction, and basic insulation in addition to supply at SELV, if limits in 8.1.4 exceeded |        | N       |
|               | The test probes are only applied to built-in appliances and fixed appliances after installation                                  |        | N       |

|          |                                                               |                 |    |
|----------|---------------------------------------------------------------|-----------------|----|
| <b>9</b> | <b>STARTING OF MOTOR-OPERATED APPLIANCES</b>                  |                 | -- |
|          | Requirements and tests are specified in part 2 when necessary | Not applicable. | N  |

|           |                                                               |                                                                                                          |    |
|-----------|---------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----|
| <b>10</b> | <b>POWER INPUT AND CURRENT</b>                                |                                                                                                          | -- |
| 10.1      | The following deviations apply:                               |                                                                                                          | -- |
|           | – appliances having UV emitters only: + 10 %; (EN 60335-2-27) |                                                                                                          | N  |
|           | – other appliances: -10%; +5% (EN 60335-2-27)                 | (see appended table 10.1)<br>Appliance is operated at DC 5V for USB port or built-in lithium ion battery | N  |

|           |                                                                                                                                                                                                 |  |    |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>11</b> | <b>HEATING</b>                                                                                                                                                                                  |  | -- |
| 11.1      | No excessive temperatures in normal use.                                                                                                                                                        |  | P  |
| 11.2      | Appliances normally placed on a floor or table are placed on the floor of the test corner with their back as near as possible to one of the walls and away from the other wall. (EN 60335-2-27) |  | P  |
|           | If the direction of the radiation is adjustable, the appliance is adjusted to the most unfavourable position of normal use.                                                                     |  | N  |
| 11.3      | Temperature rises, other than of windings, determined by thermocouples                                                                                                                          |  | P  |
|           | Temperature rises of windings determined by resistance method, unless                                                                                                                           |  | P  |
|           | the windings makes it difficult to make the necessary connections                                                                                                                               |  | N  |
| 11.4      | Heating appliances operated under normal operation at 1,15 times rated power input                                                                                                              |  | P  |
| 11.5      | Motor-operated appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage                                                                |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.

| EN 60335-2-27 |                                                                                                                                                                                                     |                       |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                  | Result                | Verdict |
| 11.6          | Combined appliances operated under normal operation at most unfavourable voltage between 0.94 and 1,06 times rated voltage                                                                          |                       | N       |
| 11.7          | The appliance is operated until steady conditions are established. (EN 60335-2-27)                                                                                                                  |                       | P       |
|               | NOTE 101 If necessary, timers are reset immediately. (EN 60335-2-27)                                                                                                                                |                       | P       |
|               | Parts operated by motors in appliances for wall mounting or ceiling mounting are fully raised and lowered five times without rest periods, or for 5 min, whichever is shorter. (EN 60335-2-27)      |                       | N       |
| 11.8          | The temperature rises shall not exceed the values given in table 3.                                                                                                                                 | (see appended tables) | P       |
|               | Sealing compound does not flow out.                                                                                                                                                                 |                       | P       |
|               | Protective devices do not operate                                                                                                                                                                   |                       | P       |
|               | The temperatures of ballast windings and their associated wiring shall not exceed the values specified in subclause 12.4 of IEC 60598-1, when measured under the conditions stated. (EN 60335-2-27) |                       | N       |
|               | The temperature rises for surfaces in contact with the skin shall not exceed those specified for handles that are continuously held in the hand. (EN 60335-2-27)                                    |                       | P       |

|           |                                                                                                |                      |    |
|-----------|------------------------------------------------------------------------------------------------|----------------------|----|
| <b>13</b> | <b>LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE</b>                          |                      | -- |
| 13.1      | Leakage current not excessive and electric strength adequate                                   |                      | P  |
|           | Heating appliances operated at 1.15 times rated power input:                                   |                      | P  |
|           | Motor-operated appliances and combined appliances supplied at 1.06 times rated voltage :       |                      | N  |
|           | Protective impedance and radio interference filters disconnected before carrying out the tests |                      | N  |
| 13.2      | Leakage current measured by means of the circuit described in figure 4 of IEC 60990            |                      | N  |
|           | Leakage current measurements                                                                   | (see appended table) | N  |
| 13.3      | Electric strength tests according to table 4                                                   |                      | P  |
|           | No breakdown during the tests                                                                  | (see appended table) | P  |

|           |                               |  |    |
|-----------|-------------------------------|--|----|
| <b>14</b> | <b>TRANSIENT OVERVOLTAGES</b> |  | -- |
|-----------|-------------------------------|--|----|


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                       |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                    | Result | Verdict |
|               | Appliances withstand the transient overvoltages to which they may be subjected                                                        |        | N       |
|               | Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6 |        | N       |
|               | No flashover during the test, unless of functional insulation                                                                         |        | N       |
|               | In case of flashover of functional insulation, the appliance complies with clause 19 with the clearance short circuited               |        | N       |

|           |                                                                                                                                                                                                              |  |    |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>15</b> | <b>MOISTURE RESISTANCE</b>                                                                                                                                                                                   |  | -- |
| 15.1      | Enclosure provides the degree of moisture protection according to classification of the appliance                                                                                                            |  | N  |
|           | Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3                                                                                        |  | N  |
|           | No trace of water on insulation which can result in a reduction of clearances and creepage distances below values specified in clause 29.                                                                    |  | N  |
| 15.1.1    | Appliances, other than IPX0, subjected to tests as specified in IEC 60529                                                                                                                                    |  | N  |
| 15.1.2    | Hand-held appliance turned continuously through the most unfavourable positions during the test                                                                                                              |  | N  |
|           | Built-in appliances installed according to the instructions                                                                                                                                                  |  | N  |
|           | Appliances placed or used on the floor or table placed on a horizontal unperforated support                                                                                                                  |  | N  |
|           | Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board                                                                                 |  | N  |
|           | For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube                                                                               |  | N  |
|           | For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube                                                                                      |  | N  |
|           | However, for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                      | Result          | Verdict |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
|        | Wall-mounted appliances, take into account the distance to the floor stated in the instructions                                         |                 | N       |
|        | Appliances with type X attachment fitted with a flexible cord as described                                                              |                 | N       |
|        | Detachable parts tested as specified                                                                                                    |                 | N       |
| 15.2   | Spillage of liquid does not affect the electrical insulation                                                                            |                 | N       |
|        | Appliances with type X attachment fitted with a flexible cord as described                                                              |                 | N       |
|        | Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable                         |                 | N       |
|        | Detachable parts removed                                                                                                                |                 | N       |
|        | Overfilling test with additional amount of water, over a period of 1 min (l) :                                                          |                 | N       |
|        | The appliance withstands the electric strength test of 16.3                                                                             |                 | N       |
|        | No trace of water on insulation that can result in a reduction of clearances and creepage distances below values specified in clause 29 |                 | N       |
| 15.3   | Appliances proof against humid conditions                                                                                               |                 | P       |
|        | Humidity test for 48 h in a humidity cabinet                                                                                            | 25 °C, 95%, 48h | P       |
|        | The appliance withstands the tests of clause 16                                                                                         |                 | P       |

|           |                                                                                     |                        |    |
|-----------|-------------------------------------------------------------------------------------|------------------------|----|
| <b>16</b> | <b>LEAKAGE CURRENT AND ELECTRIC STRENGTH</b>                                        |                        | -- |
| 16.1      | Leakage current not excessive and electric strength adequate                        |                        | N  |
|           | Protective impedance disconnected from live parts before carrying out the tests     |                        | N  |
| 16.2      | Single-phase appliances: test voltage 1,06 times rated voltage                      |                        | N  |
|           | Three-phase appliances: test voltage 1,06 times rated voltage divided by $\sqrt{3}$ | Single-phase appliance | N  |
|           | Leakage current measurements                                                        | (see appended table)   | N  |
| 16.3      | Electric strength tests according to table 7                                        | (see appended table)   | P  |
|           | No breakdown during the tests                                                       |                        | P  |

|           |                                                                    |  |    |
|-----------|--------------------------------------------------------------------|--|----|
| <b>17</b> | <b>OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS</b> |  | -- |
|-----------|--------------------------------------------------------------------|--|----|

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                               |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                            | Result | Verdict |
|               | No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use                                      |        | N       |
|               | Appliance supplied with 1,06 or 0,94 times rated voltage and the most unfavourable short-circuit or overload likely to occur in normal use applied            |        | N       |
|               | Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K |        | N       |
|               | Temperature of the winding not exceeding the value specified in table 8,                                                                                      |        | N       |

|           |                                                               |                 |    |
|-----------|---------------------------------------------------------------|-----------------|----|
| <b>18</b> | <b>ENDURANCE</b>                                              |                 | -- |
|           | Requirements and tests are specified in part 2 when necessary | Not applicable. | N  |

|           |                                                                                                                                                                                                                                |                      |    |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----|
| <b>19</b> | <b>ABNORMAL OPERATION</b>                                                                                                                                                                                                      |                      | -- |
| 19.1      | Instead of the tests specified, appliances are subjected the tests of 19.4 to 19.12, 19.101 and 19.102, as applicable. (EN 60335-2-27)                                                                                         | (see appended table) | P  |
|           | In addition, 19.2 and 19.3 are applicable for appliances having a lid but without a warning in the instructions that the appliance must not be switched on with the lid closed. (EN 60335-2-27)                                |                      | N  |
| 19.2      | Appliances having a lid that is opened in normal use are tested with the lid closed. (EN 60335-2-27)                                                                                                                           |                      | N  |
|           | The test is carried out under the conditions specified in Clause 11. Appliances having UV emitters are supplied at 0,94 times rated voltage and other appliances are operated at 0,85 times rated power input. (EN 60335-2-27) |                      | N  |
| 19.3      | The test of 19.2 is repeated but appliances having UV emitters are supplied at 1,1 times rated voltage and other appliances are operated at 1,24 times rated power input. (EN 60335-2-27)                                      |                      | N  |
| 19.4      | Test conditions as in cl. 11, any control limiting the temperature during tests of cl. 11 short-circuited                                                                                                                      |                      | P  |
| 19.5      | Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the elements sheath                                        |                      | N  |
|           | The test repeated with reversed polarity and the other end of the heating element connected to the sheath                                                                                                                      |                      | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause  | Requirement - Test                                                                                                                                                                                                                                                   | Result         | Verdict |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------|
|         | The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4                                                                                      |                | N       |
| 19.6    | Appliances with PTC heating elements tested at rated voltage, establishing steady conditions                                                                                                                                                                         |                | N       |
|         | The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures |                | N       |
| 19.7    | Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque or locking moving parts of other appliances                                                                                                                       |                | N       |
|         | Locked rotor, motor capacitors open-circuited or short-circuited, if required                                                                                                                                                                                        |                | N       |
|         | Locked rotor, capacitors open-circuited one at a time                                                                                                                                                                                                                |                | N       |
|         | Test repeated with capacitors short-circuited one at a time, if required                                                                                                                                                                                             |                | N       |
|         | Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed                                                                                                                              |                | N       |
|         | Other appliances supplied with rated voltage for a period as specified                                                                                                                                                                                               |                | N       |
|         | Winding temperatures not exceeding values specified in table 8                                                                                                                                                                                                       |                | N       |
| 19.8    | Three-phase motors operated at rated voltage with one phase disconnected                                                                                                                                                                                             |                | N       |
| 19.9    | Running overload test on appliances incorporating motors intended to be remotely or automatically controlled or liable to be operated continuously                                                                                                                   | Not applicable | N       |
| 19.10   | Series motor operated at 1,3 times rated voltage for 1 min                                                                                                                                                                                                           |                | N       |
|         | During the test, parts not being ejected from the appliance                                                                                                                                                                                                          |                | N       |
| 19.11   | Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless they comply with the conditions specified in 19.11.1                                                                |                | P       |
| 19.11.1 | Before applying the fault conditions a) to f) in 19.11.2, it is checked if circuits or parts of circuit meet both of the following conditions:                                                                                                                       |                | P       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause  | Requirement - Test                                                                                                                                                                                                 | Result | Verdict |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|         | - the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified                                                              |        | P       |
|         | - the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction in other parts of the appliance does not rely on the correct functioning of the electronic circuit                |        | N       |
| 19.11.2 | Fault conditions applied one at a time, the appliance operated under conditions specified in cl. 11, but supplied at rated voltage, the duration of the tests as specified:                                        |        | N       |
|         | a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in 29                                                                                             |        | N       |
|         | b) open circuit at the terminals of any component                                                                                                                                                                  |        | N       |
|         | c) short circuit of capacitors, unless they comply with IEC 60384-14                                                                                                                                               |        | N       |
|         | d) short circuit of any two terminals of an electronic component, other than integrated circuits. This fault condition is not applied between the two circuits of an optocoupler                                   |        | N       |
|         | e) failure of triacs in the diode mode                                                                                                                                                                             |        | N       |
|         | f) failure of an integrated circuit                                                                                                                                                                                |        | N       |
| 19.11.3 | If the appliance incorporates a protective electronic circuit which operates to ensure compliance with clause 19, the relevant test is repeated with a single fault simulated, as indicated in a) to f) of 19.11.2 |        | P       |
|         | During and after each test the following is checked:                                                                                                                                                               |        | N       |
|         | - the temperature rise of the windings do not exceed the values specified in table 8                                                                                                                               |        | N       |
|         | - the appliance complies with the conditions specified in 19.13                                                                                                                                                    |        | N       |
|         | - any current flowing through protective impedance not exceeding the limits specified in 8.1.4                                                                                                                     |        | N       |
|         | If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided all three of the following conditions are met:                               |        | N       |
|         | - the material of the printed circuit board withstands the burning test of annex E                                                                                                                                 |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**


| Clause    | Requirement - Test                                                                                                                                                                                                                                                                                                                                                                                  | Result | Verdict |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|           | - any loosened conductor does not reduce the clearances or creepage distances between live parts and accessible metal parts below the values specified in cl. 29                                                                                                                                                                                                                                    |        | N       |
|           | - the appliance withstands the tests of 19.11.2 with open-circuited conductor bridged                                                                                                                                                                                                                                                                                                               |        | N       |
| 19.11.4   | Appliances having a switch with an off position obtained by electronic disconnection, or a switch that can be placed in the stand-by mode, are subjected to the tests of 19.11.4.1 to 19.11.4.7. The tests are carried out with the appliance supplied at rated voltage, the switch being set in the position or in the stand-by mode.                                                              |        | N       |
|           | Appliance incorporating a protective electronic circuit are subjected to the tests of 19.11.4 to 19.11.7. The tests carried out after the protective electronic circuit has operated during the relevant tests of clause 19 except 19.2, 19.6 and 19.11.3. however, appliances that are operated for 30s or 5 min during test of 19.7 are not subjected to the tests for electromagnetic phenomena. |        | N       |
|           | The tests carried out with surge arresters disconnected, unless they incorporate spark gaps                                                                                                                                                                                                                                                                                                         |        | N       |
| 19.11.4.1 | The appliances is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4 being applicable. Ten discharges having appositve and ten discharges having a negative polarity and for 2 min with a negative polarity                                                                                                                                                       |        | N       |
| 19.11.4.2 | The appliances is subjected to fields in accordance with IEC 61000-4-3, that level 3 being applicable                                                                                                                                                                                                                                                                                               |        | N       |
| 19.11.4.3 | The appliance is subjected to fast transient bursts in accordance with IEC 64000-4-4. Test level 3 s applicable for signal and control lines. The test level 4 is applicable for the power supply lines. The bursts are applied for 2 min with positive polarity and for 2 min with a negative polarity                                                                                             |        | N       |
| 19.11.4.4 | The power supply terminals of the appliance are subjected to voltage surges in accordance with IEC 61000-4-5, five positive impulses and five negative impulses being applied at the selected points. The level 3 is applicable for the line-to-line coupling mode, a generator having a source impedance of 12 $\Omega$ being used.                                                                |        | N       |
|           | Earthed heating elements in class I appliances are disconnected during this test                                                                                                                                                                                                                                                                                                                    |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                     |                      |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                  | Result               | Verdict |
|               | For appliances having surge arresters incorporating spark gaps, the test is repeated at a level that is 95% of the flashover voltage                                                                                                                                                                |                      | N       |
| 19.11.4.5     | The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3 being applicable. During the test, all frequencies between 0.15 MHz to 80 MHz are covered                                                                                                            |                      | N       |
| 19.11.4.6     | The appliance is subjected to voltage dips and interruptions in accordance with IEC 61000-4-11. the durations specified in table 1 of IEC 61000-4- 11 are applied to each test level, the dips and interruptions being applied at zero crossing of the supply voltage                               |                      | N       |
| 19.11.4.7     | The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2 being applicable.                                                                                                                                                                                 |                      | N       |
| 19.11.4.8     | The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduced to a level such that the appliance ceases to respond or parts controlled by the programmable component cease to operate                                                       |                      | N       |
| 19.12         | If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A) |                      | N       |
| 19.13         | During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts                                                                                                                                                                                  |                      | P       |
|               | Temperature rises not exceeding the values shown in table 9                                                                                                                                                                                                                                         | (see appended table) | P       |
|               | Winding temperatures not exceeding the values shown in table 8                                                                                                                                                                                                                                      |                      | N       |
|               | Enclosures not deformed to such an extent that compliance with cl. 8 is impaired                                                                                                                                                                                                                    |                      | P       |
|               | If the appliance can still be operated it complies with 20.2                                                                                                                                                                                                                                        |                      | P       |
|               | Insulation, other than of class III appliance, withstand the electric strength test of 16.3, the test voltage specified in table 4:                                                                                                                                                                 |                      | P       |
|               | - basic insulation                                                                                                                                                                                                                                                                                  | 500V                 | P       |
|               | - supplementary insulation                                                                                                                                                                                                                                                                          |                      | N       |
|               | - reinforced insulation                                                                                                                                                                                                                                                                             |                      | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |              |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Result       | Verdict |
|               | The appliance does not undergo a dangerous malfunction, and                                                                                                                                                                                                                                                                                                                                                                                                                            |              | P       |
|               | no failure of protective electronic circuits, if the appliance is still operable                                                                                                                                                                                                                                                                                                                                                                                                       |              | P       |
|               | The test of 15.101 is carried out before the test of 16.3.                                                                                                                                                                                                                                                                                                                                                                                                                             |              | N       |
| 19.14         | Appliances are operated under the conditions of Clause 11. any contactor or relay contact that operates under the conditions of Clause 11 is short-circuited.                                                                                                                                                                                                                                                                                                                          |              | N       |
| 19.15         | For appliances incorporating a mains voltage selector switch, this switch is set to the lowest rated voltage position and the highest value of rated voltage is applied.                                                                                                                                                                                                                                                                                                               |              | N       |
| 19.16         | Appliances having mains connection and replaceable batteries supplied at rated voltage and operated under normal operation but with batteries removed or in any position allowed by construction                                                                                                                                                                                                                                                                                       |              | N       |
| 19.17         | For battery-operated appliances incorporating a battery using metal-ion chemistry, the battery system is operated according to the instructions and tested under the following conditions                                                                                                                                                                                                                                                                                              |              | N       |
| 19.101        | Appliances, other than those for mounting at a height more than 1,8 m above the floor, are supplied at rated voltage and operated as specified in Clause 11. When steady conditions are established, a piece of dry bleached cotton flannelette having a specific mass of 130 g/m <sup>2</sup> to 165 g/m <sup>2</sup> , a width of 100 mm and long enough to pass over the front of the appliance, is stretched over the appliance in the most unfavourable position. (EN 60335-2-27) |              | P       |
|               | The flannelette shall not smoulder or ignite within 10 s. (EN 60335-2-27)                                                                                                                                                                                                                                                                                                                                                                                                              | Not smoulder | P       |
|               | NOTE If smouldering has started, a hole will have formed in the material with its edge glowing red. Blackening without smouldering is ignored. (EN 60335-2-27)                                                                                                                                                                                                                                                                                                                         |              | N       |
| 19.102        | Appliances having discharge lamps are operated under the fault conditions specified in subclause 12.5.1 a), d) and e) of IEC 60598-1, the appliance being supplied at rated voltage. (EN 60335-2-27)                                                                                                                                                                                                                                                                                   |              | N       |
|               | The temperatures of ballast or transformer windings shall not exceed the values specified in subclause 12.5 of IEC 60598-1. (EN 60335-2-27)                                                                                                                                                                                                                                                                                                                                            |              | N       |

|    |                                  |    |
|----|----------------------------------|----|
| 20 | STABILITY AND MECHANICAL HAZARDS | -- |
|----|----------------------------------|----|


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                            |                 |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
| Clause        | Requirement - Test                                                                                                         | Result          | Verdict |
| 20.1          | Adequate stability                                                                                                         |                 | N       |
|               | Tilting test through an angle of 10° (appliance placed on an inclined plane/horizontal plane); appliance does not overturn |                 | N       |
|               | Tilting test repeated on appliances with heating elements, angle of inclination increased to 15°                           |                 | N       |
|               | Possible heating test in overturned position; temperature rise does not exceed values shown in table 9                     |                 | N       |
| 20.2          | Moving parts adequately arranged or enclosed as to provide protection against personal injury                              |                 | N       |
|               | Protective enclosures, guards and similar parts are non-detachable                                                         |                 | N       |
|               | Adequate mechanical strength and fixing of protective enclosures                                                           |                 | N       |
|               | Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard, by unexpected reclosure           | No such device. | N       |
|               | Not possible to touch dangerous moving parts with test probe                                                               |                 | N       |

|           |                                                                                                                                     |  |    |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>21</b> | <b>MECHANICAL STRENGTH</b>                                                                                                          |  | -- |
| 21.1      | Appliance has adequate mechanical strength and is constructed as to withstand rough handling                                        |  | P  |
|           | Checked by applying blows to the appliance in accordance with test Ehb of IEC 60068-2-75, spring hammer test, impact energy 0,5 J   |  | P  |
|           | If necessary, supplementary or reinforced insulation subjected to the electric strength test of 16.3                                |  | N  |
|           | If necessary, repetition of groups of three blows on a new sample                                                                   |  | N  |
|           | For emitters, including adjacent glass parts and any lens that protrude from the enclosure, the impact energy is reduced to 0,35 J. |  | N  |
|           | NOTE 101 The test is carried out on emitters and on glass parts that do not hit the floor if the appliance is dropped.              |  | N  |
| 21.2      | Accessible parts of solid insulation having strength to prevent penetration by sharp implements                                     |  | P  |
|           | The insulation is tested as specified, unless                                                                                       |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                          |        |         |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                       | Result | Verdict |
|               | the thickness of supplementary insulation is at least 1 mm and reinforced insulation is at least 2 mm                                                                                                                    |        | P       |
| 21.3          | Appliances with pins for insertion into socket-outlets with a rotating plug part are provided with a mechanical stop to prevent rotation having adequate mechanical strength and constructed to withstand rough handling |        | N       |
|               | Application of a torque of 2 Nm for 1 min does not result in rotation of the plug part after rotating it until the mechanical stop prevents further rotation, both directions checked                                    |        | N       |
| 21.101        | Guards intended to prevent inadvertent ignition of flammable material shall have adequate mechanical strength. (EN 60335-2-27)                                                                                           |        | N       |
|               | Compliance is checked by the following test. (EN 60335-2-27)                                                                                                                                                             |        | N       |
|               | The appliance is placed so that the central part of the guard is horizontal. A flat disc having a diameter of 10 cm and a mass of 2,5 kg, is placed on the centre of the guard for 1 min. (EN 60335-2-27)                |        | N       |
|               | After the test, the guard shall show no significant permanent deformation. (EN 60335-2-27)                                                                                                                               |        | N       |
| 21.102        | Parts of the appliance that are intended to support a person shall have adequate mechanical strength. (EN 60335-2-27)                                                                                                    |        | N       |
|               | Compliance is checked by the following test. (EN 60335-2-27)                                                                                                                                                             |        | N       |
|               | A mass of 135 kg, evenly distributed over an area of 30 cm x 50 cm, is placed on the surface intended to support a person for 1 min. (EN 60335-2-27)                                                                     |        | N       |
|               | After removal of the load, the appliance shall not be damaged to such an extent that compliance with this standard, in particular with Clause 29, is impaired. (EN 60335-2-27)                                           |        | N       |
|               | NOTE In case of doubt, supplementary insulation and reinforced insulation are subjected to the electric strength test of 16.3. (EN 60335-2-27)                                                                           |        | N       |

|           |                                                                                                            |  |    |
|-----------|------------------------------------------------------------------------------------------------------------|--|----|
| <b>22</b> | <b>CONSTRUCTION</b>                                                                                        |  | -- |
| 22.1      | Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**


| Clause | Requirement - Test                                                                                                                                                                                        | Result | Verdict |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| 22.2   | Stationary appliance: means to provide all-pole disconnection from the supply provided, the following means being available:                                                                              |        | N       |
|        | - a supply cord fitted with a plug                                                                                                                                                                        |        | N       |
|        | - a switch complying with 24.3                                                                                                                                                                            |        | N       |
|        | - a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided                                                                                            |        | N       |
|        | - an appliance inlet                                                                                                                                                                                      |        | N       |
|        | Singe-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor |        | N       |
| 22.3   | Appliance provided with pins: no undue strain on socket-outlets                                                                                                                                           |        | N       |
|        | Applied torque not exceeding 0.25 Nm                                                                                                                                                                      |        | N       |
|        | Pull force of 50N to each pin after the appliance has being placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1mm                                    |        | N       |
|        | Each pin subjected to a torque of 0.4Nm; the pins are not rotating unless rotating does not impair compliance with the standard                                                                           |        | N       |
| 22.4   | Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets                                                                              |        | N       |
| 22.5   | No risk of electric shock when touching the pins of the plug                                                                                                                                              |        | N       |
| 22.6   | Electrical insulation not affected by condensing water or leaking liquid                                                                                                                                  |        | N       |
|        | Electrical insulation of Class II appliances not affected in case of a hose rupture or seal leak                                                                                                          |        | N       |
| 22.7   | Adequate safeguards against the risk of excessive pressure in appliances provided with steam-producing devices                                                                                            |        | N       |
| 22.8   | Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use                    |        | N       |
| 22.9   | Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances                                                                                        |        | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                                     |                 |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                  | Result          | Verdict |
| 22.10         | Adequate insulating properties of oil or grease to which insulation is exposed                                                                                                                      |                 | N       |
| 22.11         | Location or protection of reset buttons of non-self-resetting controls is so that accidental resetting is unlikely                                                                                  |                 | N       |
|               | Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts                                               |                 | N       |
|               | Obvious locked position of snap-in devices used for fixing such parts                                                                                                                               |                 | N       |
|               | No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing                                                           |                 | N       |
|               | Tests as described                                                                                                                                                                                  |                 | N       |
| 22.12         | Handles, knobs etc. fixed in a reliable manner                                                                                                                                                      |                 | N       |
|               | Fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible                                                                                  |                 | N       |
|               | Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied                                                                                                  |                 | N       |
|               | Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied                                                                                                    |                 | N       |
| 22.13         | Unlikely that handles, when gripped as in normal use, make the operators hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only |                 | N       |
| 22.14         | No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance                                                                                                   |                 | P       |
|               | No exposed pointed ends of self tapping screws etc., liable to be touched by the user in normal use or during user maintenance                                                                      |                 | P       |
| 22.15         | Storage hooks and the like for flexible cords smooth and well rounded                                                                                                                               | No such device. | N       |
| 22.16         | Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands, no undue wear of contacts                                             | No such device. | N       |
|               | Cord reel tested with 6000 operations, as specified                                                                                                                                                 |                 | N       |
|               | Electric strength test of 16.3, voltage of 1000 V applied                                                                                                                                           |                 | N       |
| 22.17         | Spacers not removable from the outside by hand or by means of a screwdriver or a spanner                                                                                                            |                 | N       |
| 22.18         | Current-carrying parts and other metal parts resistant to corrosion under normal conditions of use                                                                                                  |                 | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                           |              |         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                        | Result       | Verdict |
| 22.19         | Driving belts not used as electrical insulation                                                                                                                                           |              | N       |
| 22.20         | Direct contact between live parts and thermal insulation effectively prevented, unless material used is non-corrosive, non-hygroscopic and non-combustible                                |              | N       |
|               | Compliance is checked by inspection and, if necessary, by appropriate test                                                                                                                |              | N       |
| 22.21         | Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless impregnated                                                                         |              | P       |
| 22.22         | Appliances not containing asbestos                                                                                                                                                        | No asbestos. | P       |
| 22.23         | Oils containing polychlorinated biphenyl (PCB) not used                                                                                                                                   |              | P       |
| 22.24         | Bare heating elements shall be supported to prevent excessive displacement occurring during normal use. The rupture of a heating element shall not give rise to a hazard. (EN 60335-2-27) |              | N       |
|               | Compliance is checked by inspection and by the following test. (EN 60335-2-27)                                                                                                            |              | N       |
|               | The heating element is cut in the most unfavourable place. The conductors shall not come into contact with accessible metal parts or fall out of the appliance(EN 60335-2-27)             |              | N       |
| 22.25         | Sagging heating conductors cannot come into contact with accessible metal parts                                                                                                           |              | N       |
| 22.26         | Insulation between parts operating at safety extra-low voltage and live parts complies with the requirements for double or reinforced insulation                                          |              | N       |
| 22.27         | Parts connected by protective impedance separated by double or reinforced insulation                                                                                                      |              | N       |
| 22.28         | Metal parts of Class II appliances conductively connected to gas pipes or in contact with water: separated from live parts by double or reinforced insulation                             |              | N       |
| 22.29         | Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation                                |              | N       |
| 22.30         | Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or                                                          |              | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                                                                                                                   |        |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                | Result | Verdict |
|               | so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete                                                                                                              |        | N       |
| 22.31         | Clearances and creepage distances over supplementary and reinforced insulation not reduced below values specified in clause 29 as a result of wear                                                                                                                                |        | N       |
|               | Clearances and creepage distances between live parts and accessible parts not reduced below values for supplementary insulation, if wires, screws etc. become loose                                                                                                               |        | N       |
| 22.32         | Supplementary and reinforced insulation designed or protected against deposition of dirt or dust                                                                                                                                                                                  |        | N       |
|               | Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2                                                                                                |        | N       |
|               | Ceramic material not tightly sintered, similar material or beads alone not used as supplementary or reinforced insulation                                                                                                                                                         |        | N       |
|               | Oxygen bomb test at 70°C for 96 h and 16 h at room temperature                                                                                                                                                                                                                    |        | N       |
| 22.33         | Conductive liquids that are or may become accessible in normal use are not in direct contact with live parts                                                                                                                                                                      |        | N       |
|               | Electrodes not used for heating liquids                                                                                                                                                                                                                                           |        | N       |
|               | For class II constructions, conductive liquids that are or may become accessible in normal use, not in direct contact with basic or reinforced insulation                                                                                                                         |        | N       |
|               | For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation                                                                                                                                             |        | N       |
| 22.34         | Shafts of operating knobs, handles, levers etc. not live, unless the shaft is not accessible when the part is removed                                                                                                                                                             |        | N       |
| 22.35         | The relaxation for stationary appliances is not applicable.                                                                                                                                                                                                                       |        | N       |
|               | Such parts being of metal, and their shafts or fixings are likely to become live in the event of an insulation fault, they are either adequately covered by insulation material, or their accessible parts are separated from their shafts or fixings by supplementary insulation |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                         |                |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                      | Result         | Verdict |
|               | This requirement does not apply to handles, levers and knobs on stationary appliances other than those of electrical components, provided they are either reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal (EN 60335-2-27) |                | N       |
| 22.36         | Handles continuously held in the hand in normal use are so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless they are separated from live parts by double or reinforced insulation                                          |                | N       |
| 22.37         | Capacitors in Class II appliances not connected to accessible metal parts, unless complying with 22.42                                                                                                                                                                                  |                | N       |
|               | Metal casings of capacitors in Class II appliances separated from accessible metal parts by supplementary insulation, unless complying with 22.42                                                                                                                                       |                | N       |
| 22.38         | Capacitors not connected between the contacts of a thermal cut-out                                                                                                                                                                                                                      |                | N       |
| 22.39         | Lamp holders used only for the connection of lamps                                                                                                                                                                                                                                      |                | N       |
| 22.40         | Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible                                         | Not applicable | N       |
| 22.41         | No components, other than lamps, containing mercury                                                                                                                                                                                                                                     |                | P       |
| 22.42         | Protective impedance consisting of at least two separate components                                                                                                                                                                                                                     |                | N       |
|               | Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited                                                                                                                                                                               |                | N       |
| 22.43         | Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur                                                                                                                                                                       |                | N       |
| 22.44         | Appliances are not allowed to have an enclosure that is shaped and decorated so that the appliance is likely to be treated as a toy by children.                                                                                                                                        |                | P       |
| 22.45         | When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.4 due to deformation as a result of an external force applied to the enclosure                                                                                                     |                | N       |
| 22.46         | Software used in protective electronic circuits is software class B or C:                                                                                                                                                                                                               |                | N       |
| 22.47         | Appliances connected to the water mains withstand the water pressure expected in normal use.                                                                                                                                                                                            |                | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**


| Clause | Requirement - Test                                                                                                                                                                                                                                                                                   | Result            | Verdict |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------|
| 22.48  | Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water                                                                                                                                                                                                    |                   | N       |
| 22.49  | For remote operation, the duration of operation shall be set before the appliance can be started, unless                                                                                                                                                                                             |                   | N       |
|        | the appliance switches off automatically or can operate continuously without hazard                                                                                                                                                                                                                  |                   | N       |
| 22.50  | Controls incorporated in the appliance take priority over controls actuated by remote operation                                                                                                                                                                                                      |                   | N       |
| 22.51  | A control on the appliance being manually adjusted to the setting for remote operation before the appliance can be operated in this mode                                                                                                                                                             |                   | N       |
|        | There is a visual indication showing that the appliance is adjusted for remote operation                                                                                                                                                                                                             |                   | N       |
|        | Manual setting and visual indication not necessary on appliances that can operate as follows, without giving rise to a hazard:                                                                                                                                                                       |                   | N       |
|        | - operate continuously,                                                                                                                                                                                                                                                                              |                   | N       |
|        | - operate automatically, or                                                                                                                                                                                                                                                                          |                   | N       |
|        | - be operated remotely                                                                                                                                                                                                                                                                               |                   | N       |
| 22.52  | Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold                                                                                                                                                   |                   | N       |
| 22.53  | Class II appliances and class III appliances that incorporate functionally earthed parts have at least double insulation or reinforced insulation between live parts and the functionally earthed parts                                                                                              |                   | N       |
| 22.54  | Button cells and batteries designated R1 not accessible without the aid of a tool, unless                                                                                                                                                                                                            | No such batteries | N       |
|        | the cover of their compartment can only be opened after at least two independent movements have been applied simultaneously                                                                                                                                                                          |                   | N       |
| 22.55  | Devices that are operated by the user to stop the intended function of the appliance, if any, shall be distinguished from other manual devices by means of shape, or size, or surface texture, or position. This requirement concerning position does not preclude use of a push on push off switch. |                   | N       |
|        | An indication when the device has been operated shall be given by:                                                                                                                                                                                                                                   |                   | N       |
|        | - tactile feedback from the actuator or tactile feedback from the appliance such as stopping of the vibration on the body of the appliance or of a part of it; or                                                                                                                                    |                   | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                                                                    |        |         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                 | Result | Verdict |
|               | - reduction in heat output; or                                                                                                                                                                                                     |        | N       |
|               | - audible and visible feedback.                                                                                                                                                                                                    |        | N       |
| 22.56         | Detachable power supply part shall be provided with the part of class III construction of the appliance.                                                                                                                           |        | N       |
| 22.57         | The properties of non-metallic materials shall not degrade from exposure to UV-C radiation generated from UV sources provided for microbiological control within the appliance such that they no longer comply with this standard. |        | P       |
| 22.58         | Appliances connected to the supply mains by an appliance inlet are provided with a cord set or a connector for attachment to a suitable flexible cord, except from                                                                 |        | N       |
|               | - appliances complying with IEC 60320-3, or                                                                                                                                                                                        |        | N       |
|               | - single phase appliances having a rated current exceeding 16 A, connected to mains by an appliance inlet complying with IEC 60309-2, or                                                                                           |        | N       |
|               | - multi-phase appliances connected to mains by an appliance inlet complying with IEC 60309-2                                                                                                                                       |        | N       |
| 22.59         | Protective extra-low voltage circuits separated by at least supplementary insulation from circuits operating at safety extra-low voltage                                                                                           |        | N       |
| 22.60         | Functional earthing terminals and functional earthing contacts not connected to the neutral terminal                                                                                                                               |        | N       |
| 22.61         | Appliance outlets complying with the standard sheets in IEC 60320-3 accessible to the user and socket outlets accessible to the user are single phase                                                                              |        | N       |
| 22.62         | Remote communication through public networks does not impair compliance with this standard                                                                                                                                         |        | N       |
| 22.101        | Appliances having a lid that has to be opened in normal use shall be constructed so that the lid does not close inadvertently. (EN 60335-2-27)                                                                                     |        | N       |
|               | Compliance is checked by the following test (EN 60335-2-27)                                                                                                                                                                        |        | N       |
|               | The appliance is placed in any normal position of use on a plane inclined at an angle of 15° to the horizontal. (EN 60335-2-27)                                                                                                    |        | N       |
|               | The lid shall remain in the open position. (EN 60335-2-27)                                                                                                                                                                         |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                   |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                | Result | Verdict |
| 22.102        | Appliances incorporating parts that are suspended or intended to be raised and lowered over a person shall incorporate a safety device to prevent injury if the suspension means fails or there is excessive travel of the part. (EN 60335-2-27)                                                  |        | N       |
|               | Compliance is checked by inspection and by manual test. (EN 60335-2-27)                                                                                                                                                                                                                           |        | N       |
| 22.103        | UV emitters intended for full body exposure and used over a person shall be protected against accidental damage. (EN 60335-2-27)                                                                                                                                                                  |        | N       |
|               | Compliance is checked by inspection and by the following test. (EN 60335-2-27)                                                                                                                                                                                                                    |        | N       |
|               | A cylindrical rod, having a diameter of 100 mm $\pm$ 1 mm and a hemispherical end, is applied with a force of 5 N. (EN 60335-2-27)                                                                                                                                                                |        | N       |
|               | It shall not be possible to touch the emitter with the rod. (EN 60335-2-27)                                                                                                                                                                                                                       |        | N       |
| 22.104        | Fixed appliances intended to be used over a person shall have means for fixing that are protected against loosening. (EN 60335-2-27)                                                                                                                                                              |        | N       |
|               | Compliance is checked by inspection and by manual test. (EN 60335-2-27)                                                                                                                                                                                                                           |        | N       |
| 22.105        | Appliances having UV emitters intended to be used by a person lying down shall be constructed so that the emission of ultraviolet radiation is automatically stopped if the timer fails. (EN 60335-2-27)                                                                                          |        | N       |
|               | Compliance is checked by the following test. (EN 60335-2-27)                                                                                                                                                                                                                                      |        | N       |
|               | The appliance is supplied at rated voltage and operated under normal operation. A fault in the timer is simulated. The emission of ultraviolet radiation shall cease before the exposure time has exceeded 110 % of the set value. (EN 60335-2-27)                                                |        | N       |
|               | NOTE Appliances having UV emitters that are intended to be used when inclined at an angle more than 35° to the vertical are considered to be appliances for use by a person lying down. (EN 60335-2-27)                                                                                           |        | N       |
| 22.106        | UV appliances shall be provided with a timer that terminates the emission of ultraviolet radiation. The timer shall be incorporated in the appliance or, for appliances intended to be permanently connected to fixed wiring, be supplied for incorporation in the wiring system. (EN 60335-2-27) |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                             |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                          | Result | Verdict |
|               | The settings marked on the timer shall be compatible with the times specified in the recommended schedule of exposure, the highest setting providing a dose not exceeding 800 J/m <sup>2</sup> (EN 60335-2-27)                              |        | N       |
|               | Compliance is checked by inspection, by measurement and by calculating the dose from the total effective irradiance determined during the test of 32.101, weighted according to the erythema action spectrum of Figure 101. (EN 60335-2-27) |        | N       |
|               | NOTE For appliances intended for permanent connection to fixed wiring, the timer may be supplied for incorporation in the wiring system. (EN 60335-2-27)                                                                                    |        | N       |
| 22.107        | Metal parts in contact with the skin and which support the body in normal use shall not be earthed. (EN 60335-2-27)                                                                                                                         |        | N       |
|               | NOTE Hinges and other parts of the enclosure that could be touched during mounting and dismounting may be earthed. (EN 60335-2-27)                                                                                                          |        | N       |
|               | Compliance is checked by inspection and by the tests specified for double insulation or reinforced insulation. (EN 60335-2-27)                                                                                                              |        | N       |
| 22.108        | Appliances intended to be fixed to a wall by screws or other permanent fixing devices shall be constructed so that the method of fixing is obvious or specified in the installation instructions. (EN 60335-2-27)                           |        | N       |
|               | Compliance is checked by inspection. (EN 60335-2-27)                                                                                                                                                                                        |        | N       |
| 22.109        | Guards intended to prevent inadvertent ignition of flammable material shall be securely attached to the appliance so that it is not possible to detach them completely without the aid of a tool. (EN 60335-2-27)                           |        | N       |
|               | Compliance is checked by inspection and by manual test. (EN 60335-2-27)                                                                                                                                                                     |        | N       |
| 22.110        | UV appliances shall incorporate a control that terminates the emission of radiation. The control shall be easily accessible to the user during exposure and be readily identified by touch and sight. (EN 60335-2-27)                       |        | N       |
|               | Compliance is checked by inspection. (EN 60335-2-27)                                                                                                                                                                                        |        | N       |

|           |                                            |  |    |
|-----------|--------------------------------------------|--|----|
| <b>23</b> | <b>INTERNAL WIRING</b>                     |  | -- |
| 23.1      | Wire ways smooth and free from sharp edges |  | P  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                                   | Result                   | Verdict |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------|
|        | Wires protected against contact with burrs, cooling fins etc.                                                                                                                                        |                          | N       |
|        | Wire holes in metal well rounded or provided with bushings.                                                                                                                                          |                          | N       |
|        | Wiring effectively prevented from coming into contact with moving parts.                                                                                                                             |                          | N       |
| 23.2   | Beads etc. on live wires cannot change their position, and are not resting on sharp edges or corners                                                                                                 | No such device           | N       |
|        | Beads inside flexible metal conduits contained within an insulating sleeve                                                                                                                           |                          | N       |
| 23.3   | Electrical connections and internal conductors movable relatively to each other not exposed to undue stress.                                                                                         |                          | N       |
|        | Flexible metallic tubes not causing damage to insulation of conductors                                                                                                                               |                          | N       |
|        | Open-coil springs not used                                                                                                                                                                           |                          | N       |
|        | Adequate insulating lining provided inside a coiled spring, the turns of which touch one another                                                                                                     |                          | N       |
|        | No damage after 10 000 for conductors flexed during normal use or 100 for conductors flexed during user maintenance                                                                                  |                          | N       |
|        | Electric strength test, 1000 V between live parts and accessible metal parts                                                                                                                         |                          | N       |
|        | The number of flexings for conductors that are only flexed when the appliance is stored is 5 000. The number of flexings for conductors flexed in normal use is increased to 50 000. (EN 60335-2-27) |                          | N       |
| 23.4   | Bare internal wiring sufficiently rigid and fixed                                                                                                                                                    | No bare internal wiring. | N       |
| 23.5   | The insulation of internal wiring withstanding the electrical stress likely to occur in normal use                                                                                                   |                          | P       |
|        | No breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation                                                                       |                          | P       |
| 23.6   | Sleeving used as supplementary insulation on internal wiring retained in position by positive means.                                                                                                 |                          | N       |
| 23.7   | The colour combination green/yellow used only for earthing conductors                                                                                                                                |                          | N       |
| 23.8   | Aluminium wires not used for internal wiring                                                                                                                                                         | No Aluminium wires used. | P       |
| 23.9   | No lead-tin soldering of stranded conductors where they are subject to contact pressure, unless                                                                                                      |                          | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                    |        |         |
|---------------|--------------------|--------|---------|
| Clause        | Requirement - Test | Result | Verdict |

|  |                                                                                                   |  |   |
|--|---------------------------------------------------------------------------------------------------|--|---|
|  | clamping means so constructed that there is no risk of bad contact due to cold flow of the solder |  | N |
|--|---------------------------------------------------------------------------------------------------|--|---|


|           |                                                                                                                                                                                                |                      |    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----|
| <b>24</b> | <b>COMPONENTS</b>                                                                                                                                                                              |                      | -- |
| 24.1      | Components comply with safety requirements in relevant IEC standards                                                                                                                           |                      | P  |
|           | List of components                                                                                                                                                                             | (see appended table) | P  |
|           | Components not tested and found to comply with relevant IEC standard for the number of cycles specified are tested in accordance with 24.1.1 to 24.1.5                                         |                      | P  |
|           | Components not tested and found to comply with relevant IEC standard, components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance |                      | N  |
| 24.1.1    | Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14, or                       |                      | N  |
|           | tested according to annex F                                                                                                                                                                    |                      | N  |
| 24.1.2    | Safety isolating transformers complying with IEC 61558-2-6, or                                                                                                                                 |                      | N  |
|           | tested according to annex G                                                                                                                                                                    |                      | N  |
| 24.1.3    | Switches complying with IEC 61058-1, the number of cycles of operation being at least 6 000.                                                                                                   |                      | P  |
|           | tested according to annex H                                                                                                                                                                    |                      | N  |
| 24.1.4    | Automatic controls complying with IEC 60730-1 with relevant part 2. The number of cycles of operation being:                                                                                   |                      | N  |
|           | - thermostats: 10 000                                                                                                                                                                          |                      | N  |
|           | - temperature limiters: 1 000                                                                                                                                                                  |                      | N  |
|           | - self-resetting thermal cut-outs: 300                                                                                                                                                         |                      | N  |
|           | - non-self-resetting thermal cut-outs: 30                                                                                                                                                      |                      | N  |
|           | - timers: 3 000                                                                                                                                                                                |                      | N  |
|           | - energy regulators: 10 000                                                                                                                                                                    |                      | N  |
| 24.1.5    | Appliance couplers complying with IEC 60320-1                                                                                                                                                  |                      | N  |
|           | However, appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3                                                                                           |                      | N  |
|           | Interconnection couplers complying with IEC 60320-2-2                                                                                                                                          |                      | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                            |                    |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                         | Result             | Verdict |
| 24.1.6        | Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable                                                                                                                                              |                    | N       |
|               | If the current flowing through the terminals of lampholders or ballasts exceeds the rated value, the terminal shall comply with subclause 15.6 of IEC 60598-1. The current for the test is 1,1 times the current measured when the appliance is operated at rated voltage. |                    | N       |
| 24.2          | Switches controlling a motor for raising or lowering part of the appliance, and switches of portable appliances having a rated current not exceeding 2 A, may be fitted in flexible cords.                                                                                 |                    | N       |
| 24.3          | Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and having a contact separation in all poles, providing full disconnection under overvoltage category III conditions                                  |                    | N       |
| 24.4          | Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1               |                    | N       |
| 24.5          | Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance and used accordingly                                                                                                                                                            | No such capacitor. | N       |
|               | Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load                                                                                             |                    | N       |
| 24.6          | Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42V                                                                                                           |                    | N       |
|               | In addition, the motors are complying with the requirements of Annex I                                                                                                                                                                                                     |                    | N       |
| 24.7          | Hose-sets for connection of appliances to the water mains, complying with IEC 61770 and supplied with the appliance                                                                                                                                                        |                    | N       |
| 24.8          | Motor running capacitors in appliances for which 30.2.3 is applicable and that are permanently connected in series with a motor winding, not causing a hazard in event of a failure                                                                                        |                    | N       |
|               | One or more of the following conditions are to be met:                                                                                                                                                                                                                     |                    | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                     |        |         |
|---------------|-----------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                  | Result | Verdict |
|               | - the capacitors are of class P2 according to IEC 60252-1                                           |        | N       |
|               | - the capacitors are housed within a metallic or ceramic enclosure                                  |        | N       |
|               | - the distance of separation of the outer surface to adjacent non-metallic parts exceeds 50 mm      |        | N       |
|               | - adjacent non-metallic parts within 50 mm withstand the needle-flame test of Annex E               |        | N       |
|               | - adjacent non-metallic parts within 50 mm classified as at least V-1 according to IEC 60695- 11-10 |        | N       |


|           |                                                                                                                                                                                                           |  |    |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>25</b> | <b>SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS</b>                                                                                                                                                      |  | -- |
| 25.1      | Appliance not intended for permanent connection to fixed wiring, means for connection to the supply:                                                                                                      |  | -- |
|           | - supply cord fitted with a plug                                                                                                                                                                          |  | N  |
|           | - an appliance inlet having at least the same degree of protection against moisture as required for the appliance                                                                                         |  | N  |
|           | - pins for insertion into socket-outlets                                                                                                                                                                  |  | N  |
| 25.2      | The appliance consists of two or more completely independent units built together in one enclosure;                                                                                                       |  | N  |
|           | Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown |  | N  |
| 25.3      | Connection of supply conductors for appliance intended to be permanently connected to fixed wiring possible after the appliance has been fixed to its support                                             |  | N  |
|           | Appliance provided with a set of terminals for the connection of cables or fixed wiring, cross-sectional areas specified in 26.6                                                                          |  | N  |
|           | Appliance provided with a set of terminals allowing the connection of a flexible cord                                                                                                                     |  | N  |
|           | Appliance provided with a set of supply leads accommodated in a suitable compartment                                                                                                                      |  | N  |
|           | Appliance provided with a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate type of cable or conduit                                          |  | N  |
| 25.4      | Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10                                                                                                 |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                     |        |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                  | Result | Verdict |
|               | Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in 29.1                                    |        | N       |
| 25.5          | Method for assemble supply cord with the appliance:                                                                                                 |        | --      |
|               | - type X attachment                                                                                                                                 |        | N       |
|               | - type Y attachment                                                                                                                                 |        | N       |
|               | - type Z attachment, if allowed in part 2                                                                                                           |        | N       |
|               | Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords                                             |        | N       |
|               | <b>Type Z attachment</b> is allowed for appliances having a mass not exceeding 3 kg. (EN 60335-2-27)                                                |        | N       |
| 25.6          | Plugs fitted with only one flexible cord                                                                                                            |        | N       |
| 25.7          | Supply cord not lighter than:                                                                                                                       |        | --      |
|               | - braided cord (code designation 60245 IEC 51),                                                                                                     |        | N       |
|               | - ordinary tough rubber sheathed cord (code designation 60245 IEC 53);                                                                              |        | N       |
|               | - fat twin tinsel cord (code designation 60227 IEC 41).                                                                                             |        | N       |
|               | - light polyvinyl chloride sheathed cord (at least 60227 IEC 52), appliances not exceeding 3 kg H05RR-F.                                            |        | N       |
|               | - ordinary polyvinyl chloride sheathed cord (at least 60227 IEC 53), other appliances                                                               |        | N       |
|               | - the appliance is constructed so that the supply cord is not likely to touch such metal parts in normal use;                                       |        | N       |
|               | - the supply cord is appropriate for higher temperatures. Type Y type Z attachment used                                                             |        | N       |
|               | Supply cords having a rubber sheath or a sheath of other material likely to be affected by ultraviolet radiation shall not be used. (EN 60335-2-27) |        | N       |
|               | NOTE 101 The emitter and the reflector are not considered to be parts that the supply cord is likely to touch in normal use. (EN 60335-2-27)        |        | N       |
| 25.8          | Cords having a nominal cross-sectional area of 0,5 mm <sup>2</sup> may be used, irrespective of their length.                                       |        | N       |
| 25.9          | Supply cord not in contact with sharp points or edges                                                                                               |        | N       |
| 25.10         | Green/yellow core for earthing purposes in Class I appliance                                                                                        |        | N       |
| 25.11         | Conductors of supply cords not consolidated by lead-tin soldering where they are subject to contact pressure, unless                                |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                | Result | Verdict |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | Clamping means so constructed that there is no risk of bad contacts due to cold flow of the solder.                                                               |        | N       |
| 25.12  | Moulding the cord to part of the enclosure does not damage the insulation of the supply cord.                                                                     |        | N       |
| 25.13  | Inlet opening so shaped as to prevent damage to the supply cord                                                                                                   |        | N       |
|        | Unless the enclosure at the inlet opening is of insulation material, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided |        | N       |
|        | If unsheathed supply cord, a similar additional bushing or lining is required, unless                                                                             |        | N       |
|        | the appliance is class 0                                                                                                                                          |        | N       |
| 25.14  | Supply cords adequately protected against excessive flexing                                                                                                       |        | N       |
|        | Flexing test:                                                                                                                                                     |        | N       |
|        | - applied force (N)                                                                                                                                               |        | N       |
|        | - number of flexings                                                                                                                                              |        | N       |
|        | The test does not result in:                                                                                                                                      |        | N       |
|        | - short circuit between the conductors                                                                                                                            |        | N       |
|        | - breakage of more than 10% of the strands of any conductor                                                                                                       |        | N       |
|        | - separation of the conductor from its terminal                                                                                                                   |        | N       |
|        | - loosening of any cord guard                                                                                                                                     |        | N       |
|        | - damage, within the meaning of the standard, to the cord or the cord guard                                                                                       |        | N       |
|        | - broken strands piercing the insulation and becoming accessible                                                                                                  |        | N       |
| 25.15  | Conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage                                                                |        | N       |
|        | The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged                                    |        | N       |
|        | Pull and torque test of supply cord, values shown in table 10: pull (N); torque (not on automatic cord reel) (Nm)                                                 |        | N       |
|        | Max. 2 mm displacement of the cord, and conductors not moved more than 1 mm in the terminals                                                                      |        | N       |
|        | Creepage distances and clearances not reduced below values specified in 29.1                                                                                      |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                         |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                      | Result | Verdict |
| 25.16         | Cord anchorages for type X attachments constructed and located so that:                                                                                                                                 |        | N       |
|               | - replacement of the cord is easily possible                                                                                                                                                            |        | N       |
|               | - it is clear how the relief from strain and the prevention of twisting are obtained                                                                                                                    |        | N       |
|               | - they are suitable for different types of cord                                                                                                                                                         |        | N       |
|               | - cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless separated from accessible metal parts by supplementary insulation                                      |        | N       |
|               | - the cord is not clamped by a metal screw which bears directly on the cord                                                                                                                             |        | N       |
|               | - at least one part of the cord anchorage securely fixed to the appliance, unless part of a specially prepared cord                                                                                     |        | N       |
|               | - screws which have to be operated when replacing the cord do not fix any other component, if applicable                                                                                                |        | N       |
|               | - if labyrinths can be bypassed the test of 25.15 is nevertheless withstood                                                                                                                             |        | N       |
|               | - for Class 0, 0I and I appliances: they are of insulating material or are provided with an insulating lining, unless a failure of the insulation of the cord does not make accessible metal parts live |        | N       |
|               | - for Class II appliances: they are of insulating material, or if of metal, they are insulated from accessible metal parts by supplementary insulation                                                  |        | N       |
| 25.17         | Adequate cord anchorages for type Y and Z attachment                                                                                                                                                    |        | N       |
| 25.18         | Cord anchorages only accessible with the aid of a tool, or                                                                                                                                              |        | N       |
|               | so constructed that the cord can only be fitted with the aid of a tool                                                                                                                                  |        | N       |
| 25.19         | Type X attachment, glands not used as cord anchorage in portable appliances                                                                                                                             |        | N       |
|               | Tying the cord into a knot or tying the cord with string not used                                                                                                                                       |        | N       |
| 25.20         | Conductors of the supply cord for type Y and Z attachment adequately additionally insulated                                                                                                             |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                                                               |        |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                                                            | Result | Verdict |
| 25.21         | Space for supply cord for type X attachment or for connection of fixed wiring constructed to permit checking of conductors with respect to correct positioning and connection before fitting any cover, no risk of damage to the conductors when fitting the cover, no contact with accessible metal parts if a conductor becomes loose, etc. |        | N       |
|               | For portable appliances, the uninsulated end of a conductor prevented from any contact with accessible metal parts, unless the end of the cord is such that the conductors are unlikely to slip free                                                                                                                                          |        | N       |
| 25.22         | Appliance inlet:                                                                                                                                                                                                                                                                                                                              |        | N       |
|               | - live parts not accessible during insertion or removal                                                                                                                                                                                                                                                                                       |        | N       |
|               | - connector can be inserted without difficulty                                                                                                                                                                                                                                                                                                |        | N       |
|               | - the appliance is not supported by the connector                                                                                                                                                                                                                                                                                             |        | N       |
|               | - is not for cold conditions if temp. rise of external metal parts exceeds 75 K, unless the supply cord is not likely to touch such metal parts                                                                                                                                                                                               |        | N       |
| 25.23         | Interconnection cords comply with the requirements for the supply cord, except as specified                                                                                                                                                                                                                                                   |        | N       |
|               | If necessary, electric strength test of 16.3                                                                                                                                                                                                                                                                                                  |        | N       |
| 25.24         | Interconnection cords not detachable without the aid of a tool if compliance with the standard is impaired when they are disconnected                                                                                                                                                                                                         |        | N       |
| 25.25         | Dimensions of pins compatible with the dimensions of the relevant socket-outlet. Dimensions of pins and engagement face in accordance with the relevant plug in IEC 60083                                                                                                                                                                     |        | N       |

|           |                                                                                                                                                                                                                        |  |    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>26</b> | <b>TERMINALS FOR EXTERNAL CONDUCTORS</b>                                                                                                                                                                               |  | -- |
| 26.1      | Appliances provided with terminals or equally effective devices for connection of external conductors                                                                                                                  |  | N  |
|           | Terminals only accessible after removal of a non-detachable cover.                                                                                                                                                     |  | N  |
|           | However, earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection                                                 |  | N  |
| 26.2      | Appliances with type X attachment and appliances for connection to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless the connections are soldered |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                                                                                                       | Result | Verdict |
|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | Screws and nuts serve only to clamp supply conductors, except                                                                                                                                                                                                            |        | N       |
|        | internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors                                                                                                                                                            |        | N       |
|        | If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone                                                                                                                                                        |        | N       |
|        | Soldering alone used, barriers provided, clearances and creepage distances satisfactory if the conductor becomes free at the soldered joint                                                                                                                              |        | N       |
| 26.3   | Terminals for type X attachment and for connection to fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure and without damaging the conductor                                                               |        | N       |
|        | Terminals for type X attachment and those for connection to fixed wiring so fixed that when tightening or loosening the clamping means:                                                                                                                                  |        | --      |
|        | - the terminal does not loosen                                                                                                                                                                                                                                           |        | N       |
|        | - internal wiring is not subjected to stress                                                                                                                                                                                                                             |        | N       |
|        | - clearances and creepage distances are not reduced below the values in 29                                                                                                                                                                                               |        | N       |
|        | Compliance checked by inspection and by the test of subclause 8.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified. Nominal diameter of thread (mm); screw category; torque (Nm)                                                     |        | N       |
| 26.4   | Terminals for type X attachment, except those with a specially prepared cord, and those for connection to fixed wiring, no special preparation of conductors required, and so constructed or placed that conductors prevented from slipping out Specially prepared cord. |        | N       |
| 26.5   | Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard                                                                                           |        | N       |
|        | Stranded conductor test, 8 mm insulation removed                                                                                                                                                                                                                         |        | N       |
|        | No contact between live parts and accessible metal parts and, for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only                                                                      |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                       |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                    | Result | Verdict |
| 26.6          | Terminals for type X attachment and for connection to fixed wiring suitable for connection of conductors with required cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm <sup>2</sup> ) |        | N       |
|               | Terminals only suitable for a specially prepared cord                                                                                                                                                                                 |        | N       |
| 26.7          | Terminals for type X attachment accessible after removal of a cover or part of the enclosure                                                                                                                                          |        | N       |
| 26.8          | Terminals for the connection to fixed wiring, including the earthing terminal, located close to each other                                                                                                                            |        | N       |
| 26.9          | Terminals of the pillar type constructed and located as specified                                                                                                                                                                     |        | N       |
| 26.10         | Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless conductors ends fitted with a device suitable for screw terminals                                                                   |        | N       |
|               | Pull test of 5 N to the connection                                                                                                                                                                                                    |        | N       |
| 26.11         | For type Y and Z attachment: soldered, welded, crimped and similar connections may be used                                                                                                                                            |        | N       |
|               | For Class II appliances: the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone                                                                                                     |        | N       |
|               | For Class II appliances: soldering, welding or crimping alone used, barriers provided, clearances and creepage distances satisfactory if the conductor becomes free                                                                   |        | N       |

|           |                                                                                                                                                   |  |    |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>27</b> | <b>PROVISION FOR EARTHING</b>                                                                                                                     |  | -- |
| 27.1      | Accessible metal parts of Class 0I and I appliances, permanently and reliably connected to an earthing terminal or contact of the appliance inlet |  | N  |
|           | Earthing terminals not connected to neutral terminal                                                                                              |  | N  |
|           | Class 0, II and III appliance have no provision for earthing                                                                                      |  | N  |
|           | Safety extra-low voltage circuits not earthed, unless protective extra-low voltage circuits                                                       |  | N  |
| 27.2      | Clamping means adequately secured against accidental loosening                                                                                    |  | N  |
|           | Terminals used for the connection of external equipotential bonding conductors allow connection of conductors of 2.5 to 6 mm <sup>2</sup> , and   |  | N  |
|           | do not provide earthing continuity between different parts of the appliance                                                                       |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                                                     | Result | Verdict |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | Conductors cannot be loosened without the aid of a tool                                                                                                                                                                |        | N       |
| 27.3   | For detachable parts that are plugged into another part of the appliance, and having an earth connection, the earth connection made before and separated after current-carrying connections when removing the part     |        | N       |
|        | For appliances with supply cord, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage                                                                        |        | N       |
| 27.4   | No risk of corrosion resulting from contact between metal of earthing terminal and other metal                                                                                                                         |        | N       |
|        | Adequate resistance to corrosion of coated or uncoated parts providing earthing continuity, other than parts of a metal frame or enclosure                                                                             |        | N       |
|        | Parts of steel providing earthing continuity provided at the essential areas with an electroplated coating, thickness at least 5µm                                                                                     |        | N       |
|        | Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure                                                                                        |        | N       |
|        | In case of aluminium alloys precautions taken to avoid risk of corrosion                                                                                                                                               |        | N       |
| 27.5   | Low resistance of connection between earthing terminal and earthed metal parts                                                                                                                                         |        | N       |
|        | This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided that clearances of basic insulation are based on the rated voltage of the appliance |        | N       |
|        | Resistance not exceeding 0,1Ω at the specified low-resistance test                                                                                                                                                     |        | N       |
| 27.6   | The printed conductors of printed circuit boards not used to provide earthing continuity in hand held appliances                                                                                                       |        | N       |
|        | They may be used in other appliances if:                                                                                                                                                                               |        | N       |
|        | - at least two tracks are used with independent soldering points and the appliance complies with requirements of 27.5 for each circuit                                                                                 |        | N       |

|           |                                                                                                             |  |    |
|-----------|-------------------------------------------------------------------------------------------------------------|--|----|
| <b>28</b> | <b>SCREWS AND CONNECTIONS</b>                                                                               |  | -- |
| 28.1      | Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                                                            | Result                    | Verdict |
|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------|
|        | Screws not of soft metal liable to creep, such as zinc or aluminium                                                                                                                                                           |                           | P       |
|        | Diameter of screws of insulating material min. 3 mm                                                                                                                                                                           | No insulating screw used. | N       |
|        | Screws of insulating material not used for any electrical connection or connections providing earthing continuity                                                                                                             |                           | N       |
|        | Screws used for electrical connections or connections providing earthing continuity screw into metal                                                                                                                          |                           | N       |
|        | Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation                                                                                                     | No such screw.            | N       |
|        | Type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw can impair basic insulation                                  |                           | N       |
|        | For screws and nuts; test as specified                                                                                                                                                                                        | (see appended table)      | P       |
| 28.2   | Electrical connections and connections providing earthing continuity constructed so that contact pressure not transmitted through insulating material liable to shrink or distort, unless shrinkage or distortion compensated |                           | N       |
|        | This requirement does not apply to electrical connections in circuits carrying a current not exceeding 0.5A                                                                                                                   |                           | N       |
| 28.3   | Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together                                                                                                                     | No such screw             | N       |
|        | Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread                                                                |                           | N       |
|        | Such screws not used if they are likely to be operated by the user or installer unless the thread is formed by a swaging action                                                                                               |                           | N       |
|        | Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection:                                                     |                           | N       |
| 28.4   | Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity                                                               |                           | N       |
|        | Rivets for electrical connections or connections providing earthing continuity secured against loosening if subjected to torsion                                                                                              |                           | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




**EN 60335-2-27**

| Clause | Requirement - Test | Result | Verdict |
|--------|--------------------|--------|---------|
|--------|--------------------|--------|---------|


|           |                                                                                                                                                                                                                                             |                      |    |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----|
| <b>29</b> | <b>CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION</b>                                                                                                                                                                                  |                      | -- |
|           | Clearances, creepage distances and solid insulation withstand electrical stress.                                                                                                                                                            | (see appended table) | P  |
|           | For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), annex J applies.                                                                                             |                      | N  |
|           | The microenvironment is pollution degree 1 under                                                                                                                                                                                            |                      | N  |
|           | No clearance or creepage distance requirements under                                                                                                                                                                                        |                      | N  |
| 29.1      | Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless                                                                                 |                      | P  |
|           | for basic insulation and functional insulation they comply with the impulse voltage test of clause 14                                                                                                                                       |                      | P  |
|           | However, if the construction is affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable |                      | P  |
|           | Impulse voltage test not applicable:                                                                                                                                                                                                        |                      | -- |
|           | - when the microenvironment is pollution degree 3                                                                                                                                                                                           |                      | N  |
|           | - for basic insulation of class 0 and class 01 appliances                                                                                                                                                                                   |                      | N  |
|           | Appliances are in overvoltage category II                                                                                                                                                                                                   |                      | P  |
|           | Clearances less than specified in table 16 not allowed for basic insulation of class 0 and class 01 appliances,                                                                                                                             |                      | N  |
|           | or if pollution degree 3 is applicable                                                                                                                                                                                                      |                      | N  |
|           | Compliance is checked by inspection and measurements as specified                                                                                                                                                                           |                      | P  |
| 29.1.1    | Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage                                                                                                                                    |                      | P  |
|           | Clearance at the terminals of tubular sheathed heating elements may be reduced to 1mm if the microenvironment is pollution degree 1                                                                                                         |                      | N  |
|           | Lacquered conductors of windings considered to be bare conductors                                                                                                                                                                           |                      | N  |
| 29.1.2    | Clearances of supplementary insulation not less than those specified for basic insulation in table 16                                                                                                                                       |                      | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                                                                      |        |         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                                                                   | Result | Verdict |
| 29.1.3        | Clearances of reinforced insulation not less than those specified for basic insulation in table 16, but using the next higher step for rated impulse voltage                                                                                                                                         |        | N       |
| 29.1.4        | For functional insulation, the values of table 16 are applicable, unless                                                                                                                                                                                                                             |        | N       |
|               | the appliance complies with clause 19 with the functional insulation short-circuited                                                                                                                                                                                                                 |        | N       |
|               | Lacquered conductors of windings considered to be bare conductors                                                                                                                                                                                                                                    |        | N       |
|               | However, clearances at crossover points are not measured                                                                                                                                                                                                                                             |        | P       |
|               | Clearance between surfaces of PTC heating elements may be reduced to 1mm                                                                                                                                                                                                                             |        | N       |
| 29.1.5        | Appliances having higher working voltage than rated voltage, the voltage used for determining clearances from table 16 is the sum of the rated impulse voltage and the difference between the peak value of the working voltage and the peak value of the rated voltage                              |        | N       |
|               | If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage |        | N       |
|               | Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation based on the working voltage used as the rated voltage in table 15                                                                                                                                    |        | N       |
| 29.2          | Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree                                                                                                                                                          |        | P       |
|               | Pollution degree 2 applies, unless                                                                                                                                                                                                                                                                   |        | N       |
|               | precautions taken to protect the insulation; pollution degree 1                                                                                                                                                                                                                                      |        | N       |
|               | insulation subjected to conductive pollution; pollution degree 3                                                                                                                                                                                                                                     |        | N       |
|               | Compliance is checked by inspection and measurements as specified                                                                                                                                                                                                                                    |        | N       |
| 29.2.1        | Creepage distances of basic insulation not less than specified in table 17                                                                                                                                                                                                                           |        | P       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**


| Clause | Requirement - Test                                                                                                                                                                | Result | Verdict |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | For pollution degree 1, creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14 |        | N       |
| 29.2.2 | Creepage distances of supplementary insulation at least as specified for basic insulation in table 17                                                                             |        | N       |
| 29.2.3 | Creepage distances of reinforced insulation at least double as specified for basic insulation in table 17                                                                         |        | N       |
| 29.2.4 | Creepage distances of functional insulation not less than specified in table 18                                                                                                   |        | N       |
|        | Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited                                                         |        | N       |
| 29.3   | Supplementary and reinforced insulation having adequate thickness, or a sufficient number of layers, to withstand the electrical stresses                                         |        | N       |
|        | Compliance checked by:                                                                                                                                                            |        | --      |
|        | - measurement, in accordance with 29.3.1, or                                                                                                                                      |        | N       |
|        | - an electric strength test in accordance with 29.3.2, or                                                                                                                         |        | N       |
|        | - an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3                                                         |        | N       |
| 29.3.1 | Supplementary insulation having a thickness of at least 1 mm                                                                                                                      |        | N       |
|        | Reinforced insulation having a thickness of at least 2 mm                                                                                                                         |        | N       |
| 29.3.2 | Each layer of material withstand the electric strength test of 16.3 for supplementary insulation                                                                                  |        | N       |
|        | Supplementary insulation consisting of at least 2 layers                                                                                                                          |        | N       |
|        | Reinforced insulation consisting of at least 3 layers                                                                                                                             |        | N       |
| 29.3.3 | The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by                                                                                                 |        | N       |
|        | the electric strength test of 16.3                                                                                                                                                |        | N       |
|        | If the temperature rise during the tests of Clause 19 does not exceed the value specified in Table 3, the test of IEC 60068-2-2 is not carried out                                |        | N       |
|        | The requirement does not apply if the insulation is provided by the envelope of an UV emitter or by the glass envelope of an IR emitter.                                          |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                                              |                |         |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                                           | Result         | Verdict |
| <b>30</b>     | <b>RESISTANCE TO HEAT AND FIRE</b>                                                                                                                                                                                                                           |                | --      |
| 30.1          | External parts of non-metallic material,                                                                                                                                                                                                                     |                | P       |
|               | parts supporting live parts, and                                                                                                                                                                                                                             |                | P       |
|               | thermoplastic material providing supplementary or reinforced insulation,                                                                                                                                                                                     |                | P       |
|               | sufficiently resistant to heat                                                                                                                                                                                                                               |                | P       |
|               | Ball-pressure test according to IEC 60695-10-2                                                                                                                                                                                                               |                | P       |
|               | External parts: at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 75°C, whichever is the higher; temperature (°C)                                                                                                     |                | P       |
|               | Parts supporting live parts: at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125°C, whichever is the higher; temperature (°C)                                                                                       |                | P       |
|               | Parts of thermoplastic material providing supplementary or reinforced insulation, 25°C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C) .....                                                                      |                | N       |
| 30.2          | Relevant parts of non-metallic material adequately resistant to ignition and spread of fire                                                                                                                                                                  |                | P       |
| 30.2.1        | Glow-wire test of IEC 60695-2-11 at 550 °C, unless                                                                                                                                                                                                           |                | P       |
|               | the material is classified at least HB40 according to IEC 60695-11-10                                                                                                                                                                                        |                | N       |
|               | Parts for which the glow-wire test cannot be carried out meet the requirements in ISO9772 for category FH3 material                                                                                                                                          |                | N       |
| 30.2.2        | For appliances that are operated while attended, parts of insulating material supporting current-carrying connections, and parts of insulating material within a distance of 3mm of such connections, are subjected to the glow-wire test of IEC 60695-2-11. | Not applicable | N       |
| 30.2.3        | Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2.                                                                                                                                                                          |                | P       |
|               | Test not applicable to conditions as specified                                                                                                                                                                                                               |                | P       |
| 30.2.3.1      | Part of insulating material supporting connections carrying a current exceeding 0.2A during normal operation, and                                                                                                                                            |                | P       |
|               | Parts of insulating material within a distance of 3mm.                                                                                                                                                                                                       |                | P       |
|               | Having a glow-wire flammability index of at least 850°C according to IEC 60695-2-12.                                                                                                                                                                         |                | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                      |        |         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                   | Result | Verdict |
| 30.2.3.2      | Part of insulating material supporting current-carrying connections, and                                                                             |        | N       |
|               | Parts of insulating material within a distance of 3mm.                                                                                               |        | N       |
|               | Subjected to glow-wire test of IEC 60695-2-11                                                                                                        |        | N       |
|               | Test not carried out on material having a glow-wire ignition temperature according to IEC 60695-2-13 as specified.                                   |        | N       |
|               | Glow-wire test of IEC 60695-2-11, the temperature being:                                                                                             |        | N       |
|               | -750°C, for connections carrying a current exceeding 0.2A during normal operation.                                                                   |        | N       |
|               | -650°C, for other connections.                                                                                                                       |        | N       |
|               | Parts that during the test produce a flame persisting longer than 2 s, tested as specified.                                                          |        | N       |
|               | If a flame persists longer than 2 s during the test, parts above the connection, as specified, subjected to the needle-flame test of annex E, unless |        | N       |
|               | The material is classified as V-0 or V-1 according to IEC 60695-11-10.                                                                               |        | N       |
| 30.2.4        | Base material of printed circuit boards subjected to needle-flame test of annex E.                                                                   |        | N       |
|               | Test not applicable to conditions as specified.                                                                                                      |        | N       |

|           |                                                             |    |
|-----------|-------------------------------------------------------------|----|
| <b>31</b> | <b>RESISTANCE TO RUSTING</b>                                | -- |
|           | Relevant ferrous parts adequately protected against rusting | P  |

|           |                                                                                                                                                      |    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| <b>32</b> | <b>RADIATION, TOXICITY AND SIMILAR HAZARDS</b>                                                                                                       | -- |
|           | Appliance does not emit harmful radiation                                                                                                            | P  |
|           | Appliance does not present a toxic or similar hazard                                                                                                 | P  |
| 32.101    | Appliances shall not present a toxic or similar hazard. Appliances having UV emitters shall not emit radiation in hazardous amounts. (EN 60335-2-27) | N  |
|           | Compliance is checked by the following test. (EN 60335-2-27)                                                                                         | N  |
|           | The appliance is provided with UV emitters that have been aged by supplying them at rated voltage for a period of (EN 60335-2-27)                    | N  |
|           | – 5 h ± 15 min for fluorescent lamps; (EN 60335-2-27)                                                                                                | N  |
|           | – 1 h ± 15 min for high-intensity discharge lamps. (EN 60335-2-27)                                                                                   | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.


## EN 60335-2-27

| Clause | Requirement - Test                                                                                                                                                                                                                                                                                                                                                                                                                                         | Result | Verdict |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | NOTE 1 A high-intensity discharge lamp is an electric discharge lamp in which the radiation-producing arc is stabilized by the wall temperature and the arc has a bulb wall loading in excess of 3 W/cm <sup>2</sup> . (EN 60335-2-27)                                                                                                                                                                                                                     |        | N       |
|        | The appliance is supplied at rated voltage and operated for approximately half the maximum exposure time allowed by the timer. The irradiance is then measured at the shortest recommended exposure distance, the measuring instrument being positioned so that the highest radiation is recorded. However, the irradiance of facial guns is measured at a distance of 100 mm ± 2 mm and calculated for the recommended exposure distance. (EN 60335-2-27) |        | N       |

|          |                                                                    |  |    |
|----------|--------------------------------------------------------------------|--|----|
| <b>A</b> | <b>ANNEX A (INFORMATIVE) ROUTINE TESTS</b>                         |  | -- |
|          | Description of routine tests to be carried out by the manufacturer |  | N  |


|          |                                                                                                                                                                                                                                                       |  |    |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>B</b> | <b>ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES</b>                                                                                                                                                                               |  | -- |
|          | The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance                                                                                                                   |  | P  |
|          | This annex does not apply to battery chargers                                                                                                                                                                                                         |  | P  |
| 3.1.9    | Appliance under the following conditions:                                                                                                                                                                                                             |  | P  |
|          | - the appliance, supplied by its fully charged battery, is operated as specified in the relevant part2;                                                                                                                                               |  | P  |
|          | - the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate;                                                                                                                                 |  | P  |
|          | - if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in the relevant part2. |  | P  |
|          | - if the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed.                                                           |  | N  |
| 3.6.2    | Part to be removed in order to discard the battery is not considered to be detachable.                                                                                                                                                                |  | P  |
| 5.101    | Appliances supplied from the supply mains tested as specified for motor-operated appliances.                                                                                                                                                          |  | P  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                                                                               |        |         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                            | Result | Verdict |
| 7.1           | Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals.                                                             |        | N       |
| 7.12          | The instructions shall give information regarding charging.                                                                                                                                   |        | P       |
|               | Details about how to remove batteries containing materials hazardous to the environment given.                                                                                                |        | P       |
| 7.15          | Markings placed on the part of the appliance connected to the supply mains.                                                                                                                   |        | P       |
| 8.2           | Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment |        | N       |
|               | If the appliance can be operated without batteries, double or reinforced insulation required                                                                                                  |        | N       |
| 11.7          | The battery is charged for the period described                                                                                                                                               |        | P       |
| 19.1          | Appliances subjected to tests of 19.101, 19.102 and 19.103                                                                                                                                    |        | P       |
| 19.101        | Appliances supplied at rated voltage for 168 h, the battery being continually charged                                                                                                         |        | P       |
| 19.102        | Short-circuiting of the terminals of the battery, being fully charged, for appliances having batteries that can be removed without the aid of a tool.                                         |        | P       |
| 19.103        | Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction                  |        | N       |
| 21.101        | Appliances having pins for insertion into socket-outlets have adequate mechanical strength, checked according to procedure 2 of IEC 68-2-32                                                   |        | N       |
|               | Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-32, the number of falls being:                                                      |        | N       |
|               | - 100, the mass of part does not exceed 250 g                                                                                                                                                 |        | N       |
|               | - 50, the mass of part exceeds 250 g                                                                                                                                                          |        | N       |
|               | After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met                                                                                                                   |        | N       |
| 22.3          | Appliances having pins for insertion into socket-outlets tested as fully assembled as possible                                                                                                |        | N       |
| 25.13         | An additional lining or bushing not required for interconnection cords operating at safety extra-low voltage                                                                                  |        | P       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                |        |         |
|---------------|--------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                             | Result | Verdict |
| 30.2          | For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies                            |        | N       |
|               | For other parts, 30.2.2 applies                                                                                                |        | N       |
| <b>C</b>      | <b>ANNEX C (NORMATIVE) AGEING TEST ON MOTORS</b>                                                                               |        | --      |
|               | Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding |        | N       |
| <b>D</b>      | <b>ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS</b>                                                                            |        | --      |
|               | Applicable to appliances having motors that incorporate thermal motor protectors                                               |        | N       |
| <b>E</b>      | <b>ANNEX E (NORMATIVE) NEEDLE-FLAME TEST</b>                                                                                   |        | --      |
|               | Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications:                             |        | --      |
| 7             | Severities                                                                                                                     |        | P       |
|               | The duration of application of the test flame is 30 s ± 1 s                                                                    |        | P       |
| 9             | Test procedure                                                                                                                 |        | P       |
| 9.1           | The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of figure 1   |        | P       |
| 9.2           | The first paragraph does not apply                                                                                             |        | N       |
|               | If possible, the flame is applied at least 10 mm from a corner                                                                 |        | N       |
| 9.3           | The test is carried out on one specimen                                                                                        |        | P       |
|               | If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test  |        | P       |
| 11            | Evaluation of test results                                                                                                     |        | P       |
|               | The duration of burning not exceeding 30 s                                                                                     |        | P       |
|               | However, for printed circuit boards, the duration of burning not exceeding 15 s                                                |        | P       |
| <b>F</b>      | <b>ANNEX F (NORMATIVE) CAPACITORS</b>                                                                                          |        | --      |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause  | Requirement - Test                                                                                                                                                                                                         | Result | Verdict |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|         | Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications: |        | N       |
| 1.5     | Terminology                                                                                                                                                                                                                |        | N       |
| 1.5.3   | Class X capacitors tested according to subclass X2                                                                                                                                                                         |        | N       |
| 1.5.4   | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 1.6     | Marking                                                                                                                                                                                                                    |        | N       |
|         | Items a) and b) are applicable                                                                                                                                                                                             |        | N       |
| 3.4     | Approval testing                                                                                                                                                                                                           |        | N       |
| 3.4.3.2 | Table II is applicable as described                                                                                                                                                                                        |        | N       |
| 4.1     | Visual examination and check of dimensions                                                                                                                                                                                 |        | N       |
|         | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 4.2     | Electrical tests                                                                                                                                                                                                           |        | N       |
| 4.2.1   | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 4.2.5   | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 4.2.5.2 | Only table IX is applicable                                                                                                                                                                                                |        | N       |
|         | Values for test A apply                                                                                                                                                                                                    |        | N       |
|         | However, for capacitors in heating appliances the values for test B or C apply                                                                                                                                             |        | N       |
| 4.12    | Damp heat, steady state                                                                                                                                                                                                    |        | N       |
|         | This subclause is applicable                                                                                                                                                                                               |        | N       |
|         | Only insulation resistance and voltage proof are checked                                                                                                                                                                   |        | N       |
| 4.13    | Impulse voltage                                                                                                                                                                                                            |        | N       |
|         | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 4.14    | Endurance                                                                                                                                                                                                                  |        | N       |
|         | Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 applicable                                                                                                                                                                    |        | N       |
| 4.14.7  | Only insulation resistance and voltage proof are checked                                                                                                                                                                   |        | N       |
|         | Visual examination, no visible damage                                                                                                                                                                                      |        | N       |
| 4.17    | Passive flammability test                                                                                                                                                                                                  |        | N       |
|         | This subclause is applicable                                                                                                                                                                                               |        | N       |
| 4.18    | Active flammability test                                                                                                                                                                                                   |        | N       |
|         | This subclause is applicable                                                                                                                                                                                               |        | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




**EN 60335-2-27**

| Clause | Requirement - Test | Result | Verdict |
|--------|--------------------|--------|---------|
|--------|--------------------|--------|---------|

|                     |                                                                                                |  |    |
|---------------------|------------------------------------------------------------------------------------------------|--|----|
| <b>G</b>            | <b>ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS</b>                                       |  | -- |
|                     | The following modifications to this standard are applicable for safety isolating transformers: |  | N  |
| 7                   | Marking and instructions                                                                       |  | N  |
| 7.1                 | Transformers for specific use marked with:                                                     |  | N  |
|                     | -name, trademark or identification mark of the manufacturer or responsible vendor              |  | N  |
|                     | -model or type reference                                                                       |  | N  |
| 17                  | Overload protection of transformers and associated circuits                                    |  | N  |
|                     | Fail-safe transformers comply with subclause 15.5 of IEC 61558-1                               |  | N  |
| 22                  | Construction                                                                                   |  | N  |
|                     | Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable                                     |  | N  |
| 29                  | Clearances, creepage distances and solid insulation                                            |  | N  |
| 29.1, 29.2 and 29.3 | The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply                 |  | N  |

|          |                                                                                                                                             |  |    |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>H</b> | <b>ANNEX H (NORMATIVE) SWITCHES</b>                                                                                                         |  | -- |
|          | Switches comply with the following clauses of IEC 61058-1, as modified:                                                                     |  | N  |
|          | -The tests of IEC 61058-1 carried out under the conditions occurring in the appliance                                                       |  | N  |
|          | -Before being tested, switches are operated 20 times without load                                                                           |  | N  |
| 8        | Marking and documentation                                                                                                                   |  | N  |
|          | Switches are not required to be marked                                                                                                      |  | N  |
|          | However, switches that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference |  | N  |
| 13       | Mechanism                                                                                                                                   |  | N  |
|          | The tests may be carried out on a separate sample                                                                                           |  | N  |
| 15       | Insulation resistance and dielectric strength                                                                                               |  | N  |
| 15.1     | Not applicable                                                                                                                              |  | N  |
| 15.2     | Not applicable                                                                                                                              |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                             |        |         |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                          | Result | Verdict |
| 15.3          | Applicable for full disconnection and micro-disconnection                                                                                                                                                   |        | N       |
| 17            | Endurance                                                                                                                                                                                                   |        | N       |
|               | Compliance is checked on three separate appliances or switches                                                                                                                                              |        | N       |
|               | For 17.2.4.4, the number of cycles is 10 000, unless otherwise specified in 24.1.3 of the relevant part 2 of EN 60335                                                                                       |        | N       |
|               | Switches for operation under no load and which can be operated only by a tool and switches operated by hand that are interlocked so that they cannot be operated under load, are not subjected to the tests |        | N       |
|               | Subclauses 17.2.2 and 17.2.5.2 not applicable                                                                                                                                                               |        | N       |
|               | The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in EN 60335-1                                                                                       |        | N       |
|               | Temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of EN 60335-1                                                                                         |        | N       |
| 20            | Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies                                                                                                             |        | N       |
|               | This clause is applicable to clearances and creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24                                          |        | N       |

|      |                                                                                                                                                            |  |    |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| I    | <b>ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE</b>                                        |  | -- |
|      | The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance:  |  | N  |
| 8    | Protection against access to live parts                                                                                                                    |  | N  |
| 8.1  | Metal parts of the motor are considered to be bare live parts                                                                                              |  | N  |
| 11   | Heating                                                                                                                                                    |  | N  |
| 11.3 | Temperature rise of the body of the motor is determined instead of the temperature rise of the windings                                                    |  | N  |
| 11.8 | Temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material |  | N  |
| 16   | Leakage current and electric strength                                                                                                                      |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                          |        |         |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                       | Result | Verdict |
| 16.3          | Insulation between live parts of the motor and its other metal parts not subjected to the test                                                                                           |        | N       |
| 19            | Abnormal operation                                                                                                                                                                       |        | N       |
| 19.1          | The tests of 19.7 to 19.9 not carried out                                                                                                                                                |        | N       |
| 19.101        | Appliance operated at rated voltage with each of the following fault conditions:                                                                                                         |        | N       |
|               | - short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit                                                                                 |        | N       |
|               | - short circuit of each diode of the rectifier                                                                                                                                           |        | N       |
|               | - open circuit of the supply to the motor                                                                                                                                                |        | N       |
|               | - open circuit of any parallel resistor, the motor being in operation                                                                                                                    |        | N       |
|               | Only one fault simulated at a time, the tests carried out consecutively                                                                                                                  |        | N       |
| 22            | Construction                                                                                                                                                                             |        | N       |
| 22.101        | For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation |        | N       |
|               | Compliance checked by the tests specified for double and reinforced insulation                                                                                                           |        | N       |

| J     | ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS                                                                                     |  | -- |
|-------|---------------------------------------------------------------------------------------------------------------------------------------|--|----|
|       | Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications: |  | N  |
| 5.7   | Conditioning of the test specimens                                                                                                    |  | N  |
|       | When production samples are used, three samples of the printed circuit board are tested                                               |  | N  |
| 5.7.1 | Cold                                                                                                                                  |  | N  |
|       | The test is carried out at -25                                                                                                        |  | N  |
| 5.7.3 | Rapid change of temperature                                                                                                           |  | N  |
|       | Severity 1 is specified                                                                                                               |  | N  |
| 5.9   | Additional tests                                                                                                                      |  | N  |
|       | This subclause is not applicable                                                                                                      |  | N  |

| K | ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES                              |  | -- |
|---|-------------------------------------------------------------------------|--|----|
|   | The information on overvoltage categories is extracted from IEC 60664-1 |  | P  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




**EN 60335-2-27**

| Clause | Requirement - Test                                                                                                                                                                     | Result | Verdict |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|        | Overvoltage category is a numeral defining a transient overvoltage condition                                                                                                           |        | P       |
|        | Equipment of overvoltage category IV is for use at the origin of the installation                                                                                                      |        | N       |
|        | Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements |        | N       |
|        | Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation                                                                          |        | P       |
|        | If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies                                                   |        | N       |
|        | Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level                    |        | N       |

|          |                                                                                                |  |    |
|----------|------------------------------------------------------------------------------------------------|--|----|
| <b>L</b> | <b>ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES</b> |  | -- |
|          | Sequences for the determination of clearances and creepage distances                           |  | P  |

|          |                                                                                                                     |  |    |
|----------|---------------------------------------------------------------------------------------------------------------------|--|----|
| <b>M</b> | <b>ANNEX M (NORMATIVE) POLLUTION DEGREE</b>                                                                         |  | -- |
|          | The information on pollution degrees is extracted from IEC 60664-1                                                  |  | -- |
|          | Pollution                                                                                                           |  | -- |
|          | The microenvironment determines the effect of pollution on the insulation, taking into account the microenvironment |  | P  |
|          | Means may be provided to reduce pollution at the insulation by effective enclosures or similar                      |  | P  |
|          | Minimum clearances specified where pollution may be present in the microenvironment                                 |  | P  |
|          | Degrees of pollution in the microenvironment                                                                        |  | P  |
|          | For evaluating creepage distances, the following degrees of pollution in the microenvironment are established:      |  | P  |
|          | - pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence     |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause | Requirement - Test | Result | Verdict |
|--------|--------------------|--------|---------|
|--------|--------------------|--------|---------|

|  |                                                                                                                                                             |  |   |
|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---|
|  | - pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected      |  | P |
|  | - pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected |  | N |
|  | - pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow                                          |  | N |

|          |                                                                                                       |  |    |
|----------|-------------------------------------------------------------------------------------------------------|--|----|
| <b>N</b> | <b>ANNEX N (NORMATIVE) PROOF TRACKING TEST</b>                                                        |  | -- |
|          | The proof tracking test is carried out in accordance with IEC 60112 with the following modifications: |  | P  |

|          |                                                                               |  |    |
|----------|-------------------------------------------------------------------------------|--|----|
| <b>O</b> | <b>ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30</b> |  | -- |
|          | Description of tests for determination of resistance to heat and fire         |  | N  |

|          |                                                                                                                             |  |    |
|----------|-----------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>P</b> | <b>ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES</b> |  | -- |
|----------|-----------------------------------------------------------------------------------------------------------------------------|--|----|

|          |                                                                                                                                                                     |  |    |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>S</b> | <b>ANNEX S (NORMATIVE) BATTERY OPERATED APPLIANCES POWERED BY BATTERIES THAT ARE NON-RECHARGEABLE OR NOT RECHARGED IN THE APPLIANCE</b>                             |  | -- |
|          | The following modifications to this standard are applicable for battery-operated appliances where the batteries are either non-rechargeable (primary batteries), or |  | N  |
|          | rechargeable batteries (secondary batteries) that are not recharged in the appliance                                                                                |  | N  |
| 5.8.1    | If the supply terminals for the connection of the battery have no indication of polarity, the more unfavourable polarity is applied                                 |  | N  |
| 5.S.101  | Appliances intended for use with a battery box are tested with the battery box supplied with the appliance or with the battery box recommended in the instructions  |  | N  |
| 5.S.102  | Appliances are tested as motor-operated appliances.                                                                                                                 |  | N  |
| 7.1      | Appliances marked with the battery voltage (V) and the polarity of the terminals, unless                                                                            |  | N  |
|          | the polarity is irrelevant                                                                                                                                          |  | N  |
|          | Appliances also marked with:                                                                                                                                        |  | N  |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**EN 60335-2-27**

| Clause       | Requirement - Test                                                                                                                                               | Result | Verdict |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
|              | – name, trade mark or identification mark of the manufacturer or responsible vendor                                                                              |        | N       |
|              | – model or type reference                                                                                                                                        |        | N       |
|              | – IP number according to degree of protection against ingress of water, other than IPX0                                                                          |        | N       |
|              | – type reference of battery or batteries                                                                                                                         |        | N       |
|              | If relevant, the positive terminal is indicated by the symbol IEC 60417-5005 and the negative terminal by the symbol IEC 60417-5006                              |        | N       |
|              | If appliances use more than one battery, they are marked to indicate correct polarity connection of the batteries                                                |        | N       |
| 7.6          | Additional symbols                                                                                                                                               |        | N       |
|              | The instructions contain the following, as applicable: N<br>– the types of batteries that may be used                                                            |        | N       |
|              | – how to remove and insert the batteries                                                                                                                         |        | N       |
|              | – non-rechargeable batteries are not to be recharged                                                                                                             |        | N       |
|              | – rechargeable batteries are to be removed from the appliance before being charged                                                                               |        | N       |
|              | – different types of batteries or new and used batteries are not to be mixed                                                                                     |        | N       |
|              | – batteries are to be inserted with the correct polarity                                                                                                         |        | N       |
|              | – exhausted batteries are to be removed from the appliance and safely disposed of                                                                                |        | N       |
|              | – if the appliance is to be stored unused for a long period, the batteries are removed                                                                           |        | N       |
|              | – the supply terminals are not to be short-circuited                                                                                                             |        | N       |
| 11.5         | Appliances are supplied with the most unfavourable supply voltage between                                                                                        |        | N       |
|              | – 0,55 and 1,0 times the battery voltage, if the appliance can be used with non-rechargeable batteries                                                           |        | N       |
|              | – 0,75 and 1,0 times battery voltage, if the appliance is designed for use with rechargeable batteries only                                                      |        | N       |
|              | The values specified in Table S.101 for the internal resistance per cell of the battery is taken into account                                                    |        | N       |
| 19.1         | The tests are carried out with the battery fully charged unless otherwise specified                                                                              |        | N       |
|              | The battery does not rupture or ignite                                                                                                                           |        | N       |
| 19.S.10<br>1 | Appliances are supplied with the voltage specified in 11.5. The supply terminals having an indication of polarity are connected to the opposite polarity, unless |        | N       |


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                                                                                                                                                                                                                                             |        |         |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                                                                                                                                          | Result | Verdict |
|               | such a connection is unlikely to occur due to the construction of the appliance                                                                                                                                                             |        | N       |
| 19.S.10<br>2  | For appliances with provision for multiple batteries, one or more of the batteries are reversed and the appliance is operated, if reversal of batteries is allowed by the construction                                                      |        | N       |
| 25.5          | The flexible leads or flexible cord used to connect an external battery or battery box in is connected to the appliance by a type X attachment                                                                                              |        | N       |
| 25.13         | This requirement is not applicable to the flexible leads or flexible cord connecting external batteries or a battery box with an appliance                                                                                                  |        | N       |
| 25.S.10<br>1  | Appliances have suitable means for connection of the battery. If the type of battery is marked on the appliance, the means of connection is suitable for this type of battery                                                               |        | N       |
| 26.5          | Terminal devices in an appliance for the connection of the flexible leads or flexible cord connecting an external battery or battery box are so located or shielded that there is no risk of accidental connection between supply terminals |        | N       |
| 30.2.3.2      | There is no battery in the area of the vertical cylinder used for the consequential needle flame test, unless                                                                                                                               |        | N       |
|               | the battery is shielded by a barrier that meets the needle flame test of Annex E, or                                                                                                                                                        |        | N       |
|               | that comprises material classified as V-0 or V-1 according to IEC 60695-11-10                                                                                                                                                               |        | N       |

|          |                                                                                                                                                                                       |  |    |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|
| <b>T</b> | <b>ANNEX T (NORMATIVE) UV-C RADIATION EFFECT ON NON-METALLIC MATERIALS</b>                                                                                                            |  | -- |
|          | Requirements for non-metallic materials subject to direct or reflected UV-C radiation exposure and whose mechanical and electrical properties are relied upon for compliance with the |  | P  |
|          | Does not apply to glass, ceramic and similar materials                                                                                                                                |  | P  |
|          | Tested as specified in ISO 4892-1 and ISO 4892-2, with the following modifications                                                                                                    |  | P  |
|          | Modifications to ISO 4892-1:                                                                                                                                                          |  | P  |
| 5.1      | Light source                                                                                                                                                                          |  | P  |
| 5.1.6    | The UV-C emitter is a low pressure mercury lamp with a quartz envelope having a continuous spectral irradiance of 10 W/m <sup>2</sup> at 254 nm                                       |  | P  |
|          | Sub-clause 5.1.6.1 and Table 1 are not applicable                                                                                                                                     |  | P  |
| 5.2      | Temperature                                                                                                                                                                           |  | P  |
| 5.2.4    | The black-panel temperature shall be 63 °C ±3 °C                                                                                                                                      |  | N  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.




| EN 60335-2-27 |                                                                                                                                  |        |         |
|---------------|----------------------------------------------------------------------------------------------------------------------------------|--------|---------|
| Clause        | Requirement - Test                                                                                                               | Result | Verdict |
| 5.3           | Humidity and wetting                                                                                                             |        | P       |
| 5.3.1         | Humidification of the chamber air is specified in part 2 when necessary                                                          |        | P       |
| 9             | Test report                                                                                                                      |        | P       |
|               | This clause is not applicable                                                                                                    |        | N       |
|               | Modifications to ISO 4892-2:                                                                                                     |        | N       |
| 7             | Procedure                                                                                                                        |        | N       |
| 7.1           | General                                                                                                                          |        | N       |
|               | At least three test specimens are tested                                                                                         |        | N       |
|               | Ten samples of internal wiring is tested                                                                                         |        | N       |
| 7.2           | Mounting the test specimens                                                                                                      |        | N       |
|               | The specimens are attached to the specimen holders such that they are not subject to any stress                                  |        | N       |
| 7.3           | Exposure                                                                                                                         |        | N       |
|               | Apparatus prepared as specified                                                                                                  |        | N       |
|               | The test specimens and, if used, the irradiance-measuring instrument are exposed for 1 000 h                                     |        | N       |
| 7.4           | Measurement of radiant exposure                                                                                                  |        | N       |
|               | If used, a radiometer is mounted and calibrated such that it measures the irradiance at the exposed surface of the test specimen |        | N       |
| 7.5           | Determination of changes in properties after exposure                                                                            |        | N       |
|               | Material properties and test methods for parts providing mechanical support or impact resistance as specified in Table T.1       |        | N       |
|               | Material properties and test method for electrical insulation of internal wiring as specified in Table T.2                       |        | N       |
| 8             | Exposure report                                                                                                                  |        | N       |
|               | This clause is not applicable                                                                                                    |        | N       |

| EN 62233 |                                                                       |                           |
|----------|-----------------------------------------------------------------------|---------------------------|
| EMF      | ANNEX 1                                                               | Verdict                   |
|          | The Tested product also complies to the requirements of EN 62233:2008 | P                         |
|          | Limit .....100%                                                       | Measured max.: 1,55%<br>P |

|                        |                              |             |                |    |             |        |
|------------------------|------------------------------|-------------|----------------|----|-------------|--------|
| 10.1                   | TABLE: Power input deviation |             |                |    |             | N      |
| Input deviation of/at: |                              | P rated (W) | P measured (W) | dP | Required dP | Remark |
| --                     |                              | --          | --             | -- | --          | --     |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



## EN 60335-2-27

| Clause | Requirement - Test                                         | Result      | Verdict         |
|--------|------------------------------------------------------------|-------------|-----------------|
| 11.8   | <b>TABLE: Heating test, thermocouples (steam emission)</b> |             | <b>P</b>        |
|        | Ambient (°C)                                               | 25,0°C      | --              |
|        | test voltage (V)                                           | 5×1,06=5,3V | P               |
|        | temperature rise dT of part/at:                            | dT (K)      | required dT (K) |
|        | Battery compartment                                        | 6,8         | 60              |
|        | Internal wire                                              | 9,5         | 80              |
|        | LED                                                        | 21,6        | 60              |
|        | Ambient                                                    | 0,3         | --              |

|      |                                                                               |        |                 |
|------|-------------------------------------------------------------------------------|--------|-----------------|
| 13.2 | <b>TABLE: LEAKAGE CURRENT MEASUREMENTS AT OPERATING TEMPERATURE</b>           |        | <b>N</b>        |
|      | heating appliances: at 1,15 times maximum rated input (W) .....               |        | --              |
|      | motor-operated and combined appliances: at 1,06 times rated voltage (V) ..... |        | --              |
|      | leakage current I between:                                                    | I (mA) | required I (mA) |
|      | --                                                                            | --     | --              |


|      |                                                                       |                  |                   |
|------|-----------------------------------------------------------------------|------------------|-------------------|
| 13.3 | <b>TABLE: ELECTRIC STRENGTH MEASUREMENTS AT OPERATING TEMPERATURE</b> |                  | <b>P</b>          |
|      | test voltage applied between:                                         | test voltage (V) | breakdown(Yes/No) |
|      | USB port to enclosure                                                 | 500              | No                |

|    |                                      |         |                  |                           |                          |                    |
|----|--------------------------------------|---------|------------------|---------------------------|--------------------------|--------------------|
| 14 | <b>TABLE: Transient overvoltages</b> |         |                  |                           |                          | <b>N</b>           |
|    | CLEARANCE BETWEEN                    | CI (mm) | Required CI (mm) | Rated impulse voltage (V) | Impulse test voltage (V) | Flashover (Yes/No) |
|    | --                                   | --      | --               | --                        | --                       | --                 |

|                            |                                       |        |                 |   |
|----------------------------|---------------------------------------|--------|-----------------|---|
| 16.2                       | TABLE: LEAKAGE CURRENT MEASUREMENTS   |        |                 | N |
|                            | at 1,06 times rated voltage (V) ..... | --     | --              |   |
| leakage current I between: |                                       | I (mA) | required I (mA) |   |
| --                         |                                       | --     | --              |   |

|      |                                              |                  |                   |
|------|----------------------------------------------|------------------|-------------------|
| 16.3 | <b>TABLE: ELECTRIC STRENGTH MEASUREMENTS</b> |                  | <b>P</b>          |
|      | test voltage applied between:                | test voltage (V) | breakdown(Yes/No) |
|      | USB port to enclosure                        | 500              | No                |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



## EN 60335-2-27

| Clause | Requirement - Test | Result | Verdict |
|--------|--------------------|--------|---------|
|--------|--------------------|--------|---------|

|                                                        |                                                                           |       |        |       |                  |                      |
|--------------------------------------------------------|---------------------------------------------------------------------------|-------|--------|-------|------------------|----------------------|
| <b>17</b>                                              | <b>TABLE: overload protection of transformers and associated circuits</b> |       |        |       |                  | <b>N</b>             |
| Temperature rise of part/at:                           |                                                                           |       |        |       | dT (K)           | Max. dT (K)          |
| Insulation of the conducts of safety extra-low voltage |                                                                           |       |        |       |                  |                      |
| Winding temperature                                    | T1(°C)                                                                    | R1(Ω) | T2(°C) | R2(Ω) | temperature (°C) | Max temperature (°C) |
| --                                                     | --                                                                        | --    | --     | --    | --               | --                   |
| --                                                     | --                                                                        | --    | --     | --    | --               | --                   |

|                        |                                                                |        |  |  |             |          |
|------------------------|----------------------------------------------------------------|--------|--|--|-------------|----------|
| <b>19.6</b>            | <b>TABLE: Abnormal operation: PTC heater over-voltage test</b> |        |  |  |             | <b>N</b> |
| Thermocouple locations |                                                                | dT (K) |  |  | Max. dT (K) |          |
| --                     |                                                                | --     |  |  | --          |          |
| --                     |                                                                | --     |  |  | --          |          |

|              |                                                     |       |                  |           |        |          |
|--------------|-----------------------------------------------------|-------|------------------|-----------|--------|----------|
| <b>19.7</b>  | <b>TABLE: Abnormal operation: The locking rotor</b> |       |                  |           |        | <b>N</b> |
| Ambient (°C) |                                                     |       | 25°C             |           |        |          |
| No.          | Component No.                                       | fault | test voltage (V) | test time | result |          |
| --           | --                                                  | --    | --               | --        | --     |          |

|                                |                                                     |  |  |  |        |             |
|--------------------------------|-----------------------------------------------------|--|--|--|--------|-------------|
| <b>19.13</b>                   | <b>TABLE: Abnormal operation: temperature rises</b> |  |  |  |        | <b>P</b>    |
|                                |                                                     |  |  |  | dT (K) | Max. dT (K) |
| Portable power supply          |                                                     |  |  |  | 1,9    | 150         |
| Room temperature               |                                                     |  |  |  | 0,3    | 150         |
| Floor temperature              |                                                     |  |  |  | 0,4    | 150         |
| Supplementary information: N/A |                                                     |  |  |  |        |             |

|                 |                          |            |                |                                     |          |
|-----------------|--------------------------|------------|----------------|-------------------------------------|----------|
| <b>24.1</b>     | <b>TABLE: COMPONENTS</b> |            |                |                                     | <b>P</b> |
| Object/part No. | Manufacturer/trade mark  | Type/model | Technical data | Mark(s) of conformity <sup>1)</sup> |          |
| Internal wire   | Various                  | VW-1       | 300V, 80°C     | UL                                  |          |
| Enclosure       | Various                  | ABS        | V0, 105°C      | UL                                  |          |
| LED             | Various                  | QZ022      | RG0            | VDE                                 |          |
| PCB             | Various                  | QZ022      | V-0, 105 °C    | UL                                  |          |
| Li-ion Battery  | --                       | QZ022      | 3.7V, 2000mAh  | Test with appliance                 |          |

<sup>1)</sup> an asterisk indicates a mark which assures the agreed level of surveillance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



## EN 60335-2-27


| Clause | Requirement - Test | Result | Verdict |
|--------|--------------------|--------|---------|
|--------|--------------------|--------|---------|

|                              |                                         |                                  |                       |          |
|------------------------------|-----------------------------------------|----------------------------------|-----------------------|----------|
| <b>28.1</b>                  | <b>TABLE: Threaded part torque test</b> |                                  |                       | <b>P</b> |
| Threaded part identification | Diameter of thread(mm)                  | Column number<br>(I, II, or III) | Applied torque ( Nm ) |          |
| Screws fixing enclosure      | 1,9                                     | II                               | 0,3                   |          |

|                          |                   |                            |            |               |            |                  |
|--------------------------|-------------------|----------------------------|------------|---------------|------------|------------------|
| 29.1                     | TABLE: Clearances |                            |            |               |            | P                |
|                          |                   | Overvoltage category.....: |            | II            |            | --               |
|                          |                   | Type of insulation:        |            |               |            | --               |
| Rated impulse voltage (V | Min. cl (mm)      | Basic                      | Functional | Supplementary | Reinforced | Verdict / Remark |
| 330                      | 0,5               | >2,0                       | --         | --            | --         | P                |
| 500                      | 0,5               | --                         | --         | --            | --         | N                |
| 800                      | 0,5               | --                         | --         | --            | --         | N                |
| 1500                     | 0,5               | --                         | --         | --            | --         | N                |
| 2500                     | 1,5               | --                         | --         | --            | --         | N                |
| 4000                     | 3,0               | --                         | --         | --            | --         | N                |
| 6000                     | 5,5               | --                         | --         | --            | --         | N                |
| 8000                     | 8,0               | --                         | --         | --            | --         | N                |
| 10000                    | 11,0              | --                         | --         | --            | --         | N                |

|                     |                                                                           |                |     |           |                |      |           |                    |    |    |         |
|---------------------|---------------------------------------------------------------------------|----------------|-----|-----------|----------------|------|-----------|--------------------|----|----|---------|
| 29.2                | TABLE: Creepage distances, basic, supplementary and reinforced insulation |                |     |           |                |      |           |                    |    |    | P       |
| Working voltage (V) | Creepage distance (mm) Pollution degree                                   |                |     |           |                |      |           | --                 |    |    | --      |
|                     | 1                                                                         | 2              |     |           | 3              |      |           | Type of insulation |    |    | --      |
|                     |                                                                           | Material group |     |           | Material group |      |           | --                 |    |    | Verdict |
|                     |                                                                           | I              | II  | IIIa/IIIb | I              | II   | IIIa/IIIb | B*                 | S* | R* |         |
| ≤50                 | 0,2                                                                       | 0,6            | 0,9 | 1,2       | 1,5            | 1,7  | 1,9       | >2,0               | -- | -- | P       |
| ≤50                 | 0,2                                                                       | 0,6            | 0,9 | 1,2       | 1,5            | 1,7  | 1,9       | --                 | -- | -- | N       |
| ≤50                 | 0,4                                                                       | 1,2            | 1,8 | 2,4       | 3,0            | 3,4  | 3,8       | --                 | -- | -- | N       |
| >50≤125             | 0,3                                                                       | 0,8            | 1,1 | 1,5       | 1,9            | 2,1  | 2,4       | --                 | -- | -- | N       |
| >50≤125             | 0,3                                                                       | 0,8            | 1,1 | 1,5       | 1,9            | 2,1  | 2,4       | --                 | -- | -- | N       |
| >50≤125             | 0,6                                                                       | 1,6            | 2,2 | 3,0       | 3,8            | 4,2  | 4,8       | --                 | -- | -- | N       |
| >125≤250            | 0,6                                                                       | 1,3            | 1,8 | 2,5       | 3,2            | 3,6  | 4,0       | --                 | -- | -- | N       |
| >125≤250            | 0,6                                                                       | 1,3            | 1,8 | 2,5       | 3,2            | 3,6  | 4,0       | --                 | -- | -- | N       |
| >125≤250            | 1,2                                                                       | 2,6            | 3,6 | 5,0       | 6,4            | 7,2  | 8,0       | --                 | -- | -- | N       |
| >250≤400            | 1,0                                                                       | 2,0            | 2,8 | 4,0       | 5,0            | 5,6  | 6,3       | --                 | -- | -- | N       |
| >250≤400            | 1,0                                                                       | 2,0            | 2,8 | 4,0       | 5,0            | 5,6  | 6,3       | --                 | -- | -- | N       |
| >250≤400            | 2,0                                                                       | 4,0            | 5,6 | 8,0       | 10,0           | 11,2 | 12,6      | --                 | -- | -- | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.






## EN 60335-2-27

| Clause      | Requirement - Test |      |      |       |       |       |       | Result |    |    | Verdict |
|-------------|--------------------|------|------|-------|-------|-------|-------|--------|----|----|---------|
| >400≤500    | 1,3                | 2,5  | 3,6  | 5,0   | 6,3   | 7,1   | 8,0   | --     | -- | -- | N       |
| >400≤500    | 1,3                | 2,5  | 3,6  | 5,0   | 6,3   | 7,1   | 8,0   | --     | -- | -- | N       |
| >400≤500    | 2,6                | 5,0  | 7,2  | 10,0  | 12,6  | 14,2  | 16,0  | --     | -- | -- | N       |
| >500≤800    | 1,8                | 3,2  | 4,5  | 6,3   | 8,0   | 9,0   | 10,0  | --     | -- | -- | N       |
| >500≤800    | 1,8                | 3,2  | 4,5  | 6,3   | 8,0   | 9,0   | 10,0  | --     | -- | -- | N       |
| >500≤800    | 3,6                | 6,4  | 9,0  | 12,6  | 16,0  | 18,0  | 20,0  | --     | -- | -- | N       |
| >800≤1000   | 2,4                | 4,0  | 5,6  | 8,0   | 10,0  | 11,0  | 12,5  | --     | -- | -- | N       |
| >800≤1000   | 2,4                | 4,0  | 5,6  | 8,0   | 10,0  | 11,0  | 12,5  | --     | -- | -- | N       |
| >800≤1000   | 4,8                | 8,0  | 11,2 | 16,0  | 20,0  | 22,0  | 25,0  | --     | -- | -- | N       |
| >1000≤1250  | 3,2                | 5,0  | 7,1  | 10,0  | 12,5  | 14,0  | 16,0  | --     | -- | -- | N       |
| >1000≤1250  | 3,2                | 5,0  | 7,1  | 10,0  | 12,5  | 14,0  | 16,0  | --     | -- | -- | N       |
| >1000≤1250  | 6,4                | 10,0 | 14,2 | 20,0  | 25,0  | 28,0  | 32,0  | --     | -- | -- | N       |
| >1250≤1600  | 4,2                | 6,3  | 9,0  | 12,5  | 16,0  | 18,0  | 20,0  | --     | -- | -- | N       |
| >1250≤1600  | 4,2                | 6,3  | 9,0  | 12,5  | 16,0  | 18,0  | 20,0  | --     | -- | -- | N       |
| >1250≤1600  | 8,4                | 12,6 | 18,0 | 25,0  | 32,0  | 36,0  | 40,0  | --     | -- | -- | N       |
| >1600≤2000  | 5,6                | 8,0  | 11,0 | 16,0  | 20,0  | 22,0  | 25,0  | --     | -- | -- | N       |
| >1600≤2000  | 5,6                | 8,0  | 11,0 | 16,0  | 20,0  | 22,0  | 25,0  | --     | -- | -- | N       |
| >1600≤2000  | 11,2               | 16,0 | 22,0 | 32,0  | 40,0  | 44,0  | 50,0  | --     | -- | -- | N       |
| >2000≤2500  | 7,5                | 10,0 | 14,0 | 20,0  | 25,0  | 28,0  | 32,0  | --     | -- | -- | N       |
| >2000≤2500  | 7,5                | 10,0 | 14,0 | 20,0  | 25,0  | 28,0  | 32,0  | --     | -- | -- | N       |
| >2000≤2500  | 15,0               | 20,0 | 28,0 | 40,0  | 50,0  | 56,0  | 64,0  | --     | -- | -- | N       |
| >2500≤3200  | 10,0               | 12,5 | 18,0 | 25,0  | 32,0  | 36,0  | 40,0  | --     | -- | -- | N       |
| >2500≤3200  | 10,0               | 12,5 | 18,0 | 25,0  | 32,0  | 36,0  | 40,0  | --     | -- | -- | N       |
| >2500≤3200  | 20,0               | 25,0 | 36,0 | 50,0  | 64,0  | 72,0  | 80,0  | --     | -- | -- | N       |
| >3200≤4000  | 12,5               | 16,0 | 22,0 | 32,0  | 40,0  | 45,0  | 50,0  | --     | -- | -- | N       |
| >3200≤4000  | 12,5               | 16,0 | 22,0 | 32,0  | 40,0  | 45,0  | 50,0  | --     | -- | -- | N       |
| >3200≤4000  | 25,0               | 32,0 | 44,0 | 64,0  | 80,0  | 90,0  | 100,0 | --     | -- | -- | N       |
| >4000≤5000  | 16,0               | 20,0 | 28,0 | 40,0  | 50,0  | 56,0  | 63,0  | --     | -- | -- | N       |
| >4000≤5000  | 16,0               | 20,0 | 28,0 | 40,0  | 50,0  | 56,0  | 63,0  | --     | -- | -- | N       |
| >4000≤5000  | 32,0               | 40,0 | 56,0 | 80,0  | 100,0 | 112,0 | 126,0 | --     | -- | -- | N       |
| >5000≤6300  | 20,0               | 25,0 | 36,0 | 50,0  | 63,0  | 71,0  | 80,0  | --     | -- | -- | N       |
| >5000≤6300  | 20,0               | 25,0 | 36,0 | 50,0  | 63,0  | 71,0  | 80,0  | --     | -- | -- | N       |
| >5000≤6300  | 40,0               | 50,0 | 72,0 | 100,0 | 126,0 | 142,0 | 160,0 | --     | -- | -- | N       |
| >6300≤8000  | 25,0               | 32,0 | 45,0 | 63,0  | 80,0  | 90,0  | 100,0 | --     | -- | -- | N       |
| >6300≤8000  | 25,0               | 32,0 | 45,0 | 63,0  | 80,0  | 90,0  | 100,0 | --     | -- | -- | N       |
| >6300≤8000  | 50,0               | 64,0 | 90,0 | 126,0 | 160,0 | 180,0 | 200,0 | --     | -- | -- | N       |
| >8000≤10000 | 32,0               | 40,0 | 56,0 | 80,0  | 100,0 | 110,0 | 125,0 | --     | -- | -- | N       |
| >8000≤10000 | 32,0               | 40,0 | 56,0 | 80,0  | 100,0 | 110,0 | 125,0 | --     | -- | -- | N       |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



| EN 60335-2-27 |                    |       |       |       |       |       |       |        |    |    |         |
|---------------|--------------------|-------|-------|-------|-------|-------|-------|--------|----|----|---------|
| Clause        | Requirement - Test |       |       |       |       |       |       | Result |    |    | Verdict |
| >8000≤10000   | 64,0               | 80,0  | 112,0 | 160,0 | 200,0 | 220,0 | 250,0 | --     | -- | -- | N       |
| >10000≤12500  | 40,0               | 50,0  | 71,0  | 100,0 | 125,0 | 140,0 | 160,0 | --     | -- | -- | N       |
| >10000≤12500  | 40,0               | 50,0  | 71,0  | 100,0 | 125,0 | 140,0 | 160,0 | --     | -- | -- | N       |
| >10000≤12500  | 80,0               | 100,0 | 142,0 | 200,0 | 250,0 | 280,0 | 320,0 | --     | -- | -- | N       |

B=Basic, S=Supplementary and R=Reinforced

|                     |                                         |                |      |            |                |       |           |                 |
|---------------------|-----------------------------------------|----------------|------|------------|----------------|-------|-----------|-----------------|
| 29.2                | TABLE: Creepage distances, functional   |                |      |            |                |       |           | P               |
| Working voltage (V) | Creepage distance (mm) Pollution degree |                |      |            |                |       |           | --              |
|                     | 1                                       | 2              |      |            | 3              |       |           | --              |
|                     |                                         | Material group |      |            | Material group |       |           | Verdict /Remark |
|                     |                                         | I              | II   | IIIa/IIIb  | I              | II    | IIIa/IIIb |                 |
| ≤50                 | 0,2                                     | 0,6            | 0,8  | 1,1        | 1,4            | 1,6   | 1,8       | P               |
| >50≤125             | 0,3                                     | 0,7            | 1,0  | 1,4        | 1,8            | 2,0   | 2,2       | N               |
| >125≤250            | 0,4                                     | 1,0            | 1,4  | <b>2,0</b> | 2,5            | 2,8   | 3,2       | N               |
| >250≤400            | 0,8                                     | 1,6            | 2,2  | 3,2        | 4,0            | 4,5   | 5,0       | N               |
| >400≤500            | 1,0                                     | 2,0            | 2,8  | 4,0        | 5,0            | 5,6   | 6,3       | N               |
| >500≤800            | 1,8                                     | 3,2            | 4,5  | 6,3        | 8,0            | 9,0   | 10,0      | N               |
| >800≤1000           | 2,4                                     | 4,0            | 5,6  | 8,0        | 10,0           | 11,0  | 12,5      | N               |
| >1000≤1250          | 3,2                                     | 5,0            | 7,1  | 10,0       | 12,5           | 14,0  | 16,0      | N               |
| >1250≤1600          | 4,2                                     | 6,3            | 9,0  | 12,5       | 16,0           | 18,0  | 20,0      | N               |
| >1600≤2000          | 5,6                                     | 8,0            | 11,0 | 16,0       | 20,0           | 22,0  | 25,0      | N               |
| >2000≤2500          | 7,5                                     | 10,0           | 14,0 | 20,0       | 25,0           | 28,0  | 32,0      | N               |
| >2500≤3200          | 10,0                                    | 12,5           | 18,0 | 25,0       | 32,0           | 36,0  | 40,0      | N               |
| >3200≤4000          | 12,5                                    | 16,0           | 22,0 | 32,0       | 40,0           | 45,0  | 50,0      | N               |
| >4000≤5000          | 16,0                                    | 20,0           | 28,0 | 40,0       | 50,0           | 56,0  | 63,0      | N               |
| >5000≤6300          | 20,0                                    | 25,0           | 36,0 | 50,0       | 63,0           | 71,0  | 80,0      | N               |
| >6300≤8000          | 25,0                                    | 32,0           | 45,0 | 63,0       | 80,0           | 90,0  | 100,0     | N               |
| >8000≤10000         | 32,0                                    | 40,0           | 56,0 | 80,0       | 100,0          | 110,0 | 125,0     | N               |
| >10000≤12500        | 40,0                                    | 50,0           | 71,0 | 100,0      | 125,0          | 140,0 | 160,0     | N               |

|           |                            |                       |                          |                                  |
|-----------|----------------------------|-----------------------|--------------------------|----------------------------------|
| 30.1      | TABLE: Ball-pressure tests |                       |                          | P                                |
| part      |                            | test temperature (°C) | Impression diameter (mm) | Allowed impression diameter (mm) |
| Enclosure |                            | 125,0                 | 0,88                     | <2                               |

|           |                       |                       |                                       |    |
|-----------|-----------------------|-----------------------|---------------------------------------|----|
| 30.2      | TABLE: Glow-wire test |                       |                                       | P  |
| Part      |                       | Test temperature (°C) | Self-extingusished in the further 30s | -- |
| Enclosure |                       | 550                   | Not burning                           | P  |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



**APPENDIX A**  
**PHOTO(S) OF PRODUCT**  
Front View of Sample



Back View of Sample



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.



Side View of Sample



Internal View of Sample



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.

Front View of Model: QZ036



Internal View of Model: QZ036



----- End of Report -----

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ENC, this document cannot be reproduced except in full with our prior written permission. The document is available on request and the brief information for its validation can be assessable and confirmed at <http://www.enc-lab.com>.